Active Temperature compensation for MEMS capacitive sensor

Cuong Do, *Member, IEEE*, Ashwin A. Seshia, *Senior Member, IEEE*

Abstract — Temperature variation is one of the most crucial factors that need to be cancelled in MEMS sensors. Many traditional methodologies require an additional circuit to compensate for temperature. This work describes a new active temperature compensation method for MEMS capacitive strain sensor without any additional circuit. The proposed method is based on a complement 2-D capacitive structure design. It consumes zero-power, which is essential toward the realization of a low-power temperature-compensated sensor in battery-powered or energy-harvesting applications. The gauge factor of the developed MEMS capacitive strain sensor is 7. The best result showing a capacitance variation of 1 ppm/°C compared with 13 ppm/°C on conventional design.

Index Terms—Active temperature compensation, Complement 2-D capacitive structure, Strain gauge.

I. Introduction

CAPACITOR is a device that consists of two electrodes separated by an insulator. For parallel plate capacitors, the capacitance can be expressed as:

$$C = (A\epsilon_0\epsilon_r)/d \quad (1)$$

where C is the capacitance, A is the overlapping area of the two plates, ϵ_0 is the permittivity of free space, ϵ_r is the relative permittivity of the dielectric material, and d is the distance between the plates. Capacitive sensors are realized by varying any of the three parameters of a capacitor: the distance between two plates, overlapped area of plates, and the dielectric constant of an insulator.

Based on those physical changes, a wide variety of capacitive sensors have been developed, ranging from proximity sensing [1-5], position sensing [6, 7], humidity sensing [8, 9], tilt sensing [10, 11], strain sensing [12, 13, 14], etc. As the capacitance is not dependent on the properties of the plate material, and thermal expansion is generally isotropic in three dimensions, capacitive sensors are generally considered to having low-temperature dependence compared with other sensor methods, such as resistive based [15] or resonant based [16]. However, in sensing applications where the capacitive sensor adheres to package or other host materials, such as strain gauge as demonstrated in Fig. 1, the coefficient of thermal capacitance (CTC) will be affected and proportional to the

Fig. 1. Thermal expansion of host structure under test

complex combination of the coefficient of thermal expansion (CTE) of adhesive and host materials.

Most materials expand and contract when the temperature changes. Every material has its own coefficient of thermal expansion (CTE), the change in length with temperature for a solid material can be expressed as

$$\alpha(T) = [L_T - L_0]/[L_0\Delta T] \quad (2)$$

where L_0 and L_T represent, respectively, the initial and final lengths with temperature change ΔT , the CTE, $\alpha(T)$, is usually found to be nonlinear with temperature [17]. For example, silicon, which is widely used in MEMS structure, has the CTE found to be varied from 2.57 ppm/K at 293 K to 4.33 ppm/K at 1000 K [18].

In practice, MEMS silicon structure is usually glued onto a package carrier (e.g. polyimide, metals) using an adhesive material (e.g. super glue, M-bond). Furthermore, the whole strain gauge is then bonded onto a host infrastructure material (e.g. concrete, steel, aluminium, glass). Thus, the temperature effect on the capacitive sensor becomes extremely complex in

Manuscript received

Cuong Do was with the Engineering Department at the University of Cambridge. He is now with the College of Engineering and Computer Science, VinUniversity, Hanoi, Vietnam (email: cuong.dd@vinuni.edu.vn)

Ashwin A. Seshia is with the Engineering Department at the University of Cambridge, Cambridge, UK (email: aas41@eng.cam.ac.uk)

TABLE I

COEFFICIENT OF THERMAL EXPANSION (CTE) OF SOME MATERIALS RELATED TO STRAIN SENSING

Materials	CTE (ppm/K)
Polyimide	~20
Aluminium	~23
Super glue	~100
Steel	~11
Concrete	~12
Glass	~8.5

strain sensing applications. CTE of some of the above-mentioned materials can be found in Table. I [17, 19]. The CTEs of these materials are a few times higher than that of silicon. Therefore, temperature effect will be exacerbated on to the sensor, including MEMS capacitive strain sensor.

Here, we introduce for the first time, an active compensation method based on a complement 2-D capacitive structure design to help to reduce the thermal expansion issue on MEMS capacitive sensor without any additional complex compensation circuit.

II. DESIGN CONCEPT

A concept of 2-D complement capacitive comb structure design is demonstrated in Fig. 2. The structures AB1 and AB2 are designed identically in term of distance, the number of interdigitated fingers, thickness, overlapping area and gap. The only difference is the fingers orientation layout, as clearly seen in Fig. 2. When the whole structure is heated, the substrate is expanded to all directions [20]. By neglecting the fringing effect, the capacitance between AB1 and AB2, C_{AB1} , C_{AB2} can be found as:

$$C_{AB1} = \frac{2N\epsilon_r h(x - \Delta x_1)}{g} \quad (3)$$

$$C_{AB2} = \frac{2N\epsilon_r h(x + \Delta x_2)}{g} \quad (4)$$

where N is the number of interdigitated fingers on each branch, h is the thickness of the fingers, x is the initial overlapping length between fingers, g is the gap between two adjacent fingers, and Δx_1 , Δx_2 are the changes in the overlapping between fingers due to substrate expansion under heating. It is

Fig. 2. An illustration of a temperature compensated capacitive sensor based on complement 2-D capacitive comb structure design.

Fig. 3. MIDIS™ MEMS platform process by CMC.

noted that, in a comb structure, the fringing effect is independent with the overlapping area. The substrate contraction during cooling is following exactly similar behavior.

If the substrate is isotropic, the expansion to x and y directions should be equal and hence, $\Delta x_1 = \Delta x_2$. When B1 and B2 are connected, the capacitance factor caused by thermal expansion on two branches can be cancelled out and thus the total capacitance is independent of temperature variation.

$$C_T = C_{AB1} + C_{AB2} = \frac{4N\epsilon_r h(x)}{g} \quad (5)$$

III. THE SENSOR

Based on the concept discussed in the previous section, MEMS capacitive sensors have been developed and fabricated on the MIDIS™ Platform, which is being offered as Multi-Project-Wafer (MPW) service through CMC Microsystems [21]. The process is 1.5 μm minimum feature size, 1.5 μm minimum gap, 30 μm silicon thickness membrane and wafer-level vacuum packaged. More details of the process are shown in Fig. 3. Fig. 4 shows the SEM picture of the fabricated Design 1 before it was encapsulated. The design follows the thermal expansion compensation concept, as discussed above. Branches AB3 and AB4 are similar to AB1 and AB2, respectively. B1, B2, B3, B4 are connected by a top metal layer after encapsulation. In order to achieve a high-performance sensor

Fig. 4. SEM picture of the developed MEMS capacitive sensor with temperature compensation technique, Design 1.

Fig. 5. SEM picture of the developed MEMS capacitive sensor without temperature compensation technique, Design 2.

TABLE II

DIMENSIONS AND ESTIMATED PARAMETERS OF THE MEMS CAPACITIVE SENSORS

Description	Design 1	Design 2
Chip size	1250 x 1250 μm^2	1150 x 820 μm^2
Device thickness, h	30 μm	30 μm
Total number of fingers, N_T	2720	1428
Capacitor finger gap, g	1.5 μm	1.5 μm
Finger overlap, x	7.5 μm	10 μm
Estimated comb capacitance	7.22 pF	5.05 pF
Estimated parallel parasitic	1.8 pF	1.3 pF

with high capacitive and sensitivity, the interdigitated comb fingers are designed in a compact form, as shown in the zoom-in sub-figure. The gap between fingers is designed at the process minimum of $g = 1.5 \mu\text{m}$. To reduce the parallel plate parasitic, the maximum gap is advised to be as big as possible. However, the maximum distance between adjacent structures of this process is only at $5 \mu\text{m}$, hence some unwanted high parasitic capacitance is predicted in this design. This will affect the sensitivity and resolution of the sensors. However, the 2-D complement capacitive concept described above is still applicable to the parallel plate capacitor. Therefore, the parasitic variations will also be cancelled out under temperature variation.

In order to evaluate the effectiveness of the concept, a normal design without temperature compensation technique has also been developed to compare and contrast with the one in Fig. 4. The SEM picture is shown in Fig. 5. The general design structure concept of the interdigitated comb fingers layout is annotated on the top of the SEM figure. When temperature varies, the MEMS structure is expanded or contracted. Both AB1 and AB2 capacitance will either increase or decrease at the same time with temperature.

Table II shows designed dimensions and some estimated parameters of the two MEMS capacitive designs. The parallel

Fig. 6. Cantilever beam bending test setup for MEMS strain sensors.

plate parasitic is relatively high due to the limited maximum gap in this process. It will eventually affect the sensitivity of the sensors as it travels in the opposite direction and inherits a nonlinear capacitance versus distance relationship.

This is not an ideal comparison as Design 2 is not fully-symmetrical as Design 1. However, the total number of finger, N_T , fingers gap, g , and the finger overlap, x , are mainly related to the range and resolution of the sensors. The temperature sensitivity is mainly related to the relative finger overlapping, Δx . Hence, this relative comparison is still eligible to prove the concept.

IV. EXPERIMENTAL RESULTS AND DISCUSSION

The fabricated sensors are attached by M-bond 200 on a cantilever beam bending test setup for strain sensing measurement, as shown in Fig. 6. Both sensors are on the same die. The die encapsulation is grounded to remove parasitic capacitance of top metal layer, which is AlCu. The chip is wire-bonded to a flexible PCB board for external connection. A cantilever beam with a length of L , and thickness of t is anchored at one end with the MEMS sensors located at a position of p from the anchor. The beam material is steel with length, L , of 220 mm, thickness, t , of 3 mm, and the sensors are located at $p = 35 \text{ mm}$. The displacement is measured by a micrometre, and the corresponding strain relationship can be found in the figure.

Fig. 7. Real-time monitoring and data logging strain sensing setup.

TABLE III
EVAL-AD7150EBZ BOARD SETTING

Parameters	Value	Unit
Excitation frequency	32	kHz
Conversion time (sampling rate)	5 (200)	ms (Hz)
Input range	500	fF
$\Delta\Sigma$ CDC Resolution	12	bit
1-bit resolution	0.012	fF

Fig. 7 presents the real-time measurement setup using a commercial capacitive interface data acquisition board: EVAL-AD7150EBZ for capacitance-to-digital converter. It has two independent input channels. Hence two developed designs could be tested at the same time. Real-time graphic monitoring and data logging software is also provided.

Parameters setup for EVAL-AD7150EBZ board is shown in Table III. The input range is set to the lowest possible range setting (500 fF). At this setting and with 12-bit CDC, the 1 bit resolution is 0.012 fF. The $\Sigma\Delta$ modulator helps to significantly minimize the noise and therefore helps to enhance the measurement accuracy. The conversion time is set by default at 5 ms per sample.

The measured capacitance of the two designs are 10 pF and 7.1 pF for Design 1 and 2, respectively. They are $\sim 10\%$ higher than the estimated values (including comb and parallel parasitic capacitance). The differences could be contributed by the wire bonds, PCB and coaxial cable connections parasitic.

Fig. 8 presents the measured output versus an applied input strain for both designs up to 800 $\mu\epsilon$ with a nonlinearity of less than 2% of full scale. Design 1 has a slightly higher sensitivity at ~ 0.07 fF/ $\mu\epsilon$ than Design 2, which is measured at 0.05 fF/ $\mu\epsilon$. The equivalent Gauge Factors are found at 7 for both designs.

The temperature dependence characterization is carried out with an environmental chamber to evaluate the temperature compensation effectivity of the concept. Both designs are on the same dice, which adheres to a steel bar with M-bond 200 glue. Fig. 9 shows the capacitance changes of the two designs for 10 samples each, with temperature from 25 to 130°C. Error bars

Fig. 8. Capacitance changes versus strain characterization of two developed MEMS sensors.

Fig. 9. Capacitance changes versus temperature.

are around 0.03 to 0.05 fF. The CTC of Design 2 (conventional design) is found at ~ 13 ppm/ $^{\circ}\text{C}$, which is similar to the CTE of steel of ~ 11 ppm/ $^{\circ}\text{C}$ as seen in Table. I. Whereas, the CTC of Design 1 (where compliment capacitive structure is utilized) is found at only 1 ppm/ $^{\circ}\text{C}$. It is clearly shown the effectivity of the proposed method to reduce the temperature effect on MEMS capacitive strain sensor.

V. CONCLUSION

This paper presents the design concept and characterization results for a new method to compensate for the temperature effect of capacitance strain gauge. The sensors were fabricated on silicon MEMS technology. The gauge factor is measured at 7. The thermal effect has been assessed at a temperature up to 130°C. The technique requires no addition circuit or special fabrication process.

The proposed method improves the CTC of the sensor by 13 times compared with the conventional design. Future work is required for the development of low-power front-end capacitive readout to improve resolution and sensitivity. Characterizations of capacitive strain gauges for higher temperature operation (up to 1000°C), long-term stability, and degradation mechanisms are also required in future studies.

This method is also applicable to other types of capacitive sensor, including proximity sensing, position sensing, humidity sensing, and tilt sensing. Further research on this topic on how to effectively employ this technique in those applications is being carried out.

If we were to design this study again, we would make Design 2 as fully-symmetrical as Design 1 to have a better comparison.

REFERENCES

- [1] Ojuroye, Olivia O., et al. "Embedded capacitive proximity and touch sensing flexible circuit system for electronic textile and wearable systems." *IEEE Sensors Journal*, vol. 19, no. 16, 2019.
- [2] J. Wang, Jiaqi, Z. Zheng, J. Chan, and J.T. Yeow, "Capacitive micromachined ultrasound transducers for intravascular ultrasound imaging." *Microsystems & Nanoengineering*, vol. 6, no. 1, pp. 1-13, 2020.
- [3] Anzinger, Sebastian, et al. "Low Power Capacitive Ultrasonic Transceiver Array for Airborne Object Detection." in *IEEE 33rd*

International Conference on Micro Electro Mechanical Systems (MEMS), 2020.

- [4] T. Emadi, and A.B. Douglas, "A novel 6×6 element MEMS capacitive ultrasonic transducer with multiple moving membranes for high performance imaging applications." *Sensors and Actuators A: Physical*, vol. 222, pp. 309-313, 2015.
- [5] R.N. Miles, W. Cui, Q.T. Su, and D. Homencovschi, "A MEMS low-noise sound pressure gradient microphone with capacitive sensing", *Journal of Microelectromechanical Systems*, vol. 24, no. 1, pp. 241-248, 2015.
- [6] Dong, Xianshan, et al. "Research on temperature characteristic of parasitic capacitance in MEMS capacitive accelerometer." *Sensors and Actuators A: Physical*, vol. 285, pp. 581-587, 2019.
- [7] E.E. Aktakka, and K. Najafi, "A six-axis micro platform for in situ calibration of MEMS inertial sensors", in *Proc. IEEE MEMS 29th International Conference*, 2016.
- [8] Mutharpavalar, Ashaashvini, A. Y. Ahmed, and Nursyarizal Mohd Nor. "Design, Modeling and Simulation of MEMS Resonator for Humidity Sensor Application." in *Prof. IEEE Sensors Applications Symposium (SAS)*, 2020.
- [9] N. Lazarus, S.S. Bedair, C.C. Lo, and G.K. Fedder, "CMOS-MEMS capacitive humidity sensor", *Journal of Microelectromechanical Systems*, vol. 19, no. 1, pp. 183-191, 2010.
- [10] Rao, Kang, et al. "A high-resolution area-change-based capacitive MEMS tilt sensor." *Sensors and Actuators A: Physical*, vol. 313, 2020.
- [11] L. Zhao, and E.M. Yeatman, "Micro capacitive tilt sensor for human body movement detection", in *Proc. Body Sensor Networks*, pp. 195-200, 2007.
- [12] Shirhatti, Vijay, et al. "High-range noise immune supersensitive graphene-electrolyte capacitive strain sensor for biomedical applications." *Nanotechnology*, vol. 30, no. 47, 2019.
- [13] M. Suster, J. Guo, N. Chaimanonart, W. Ko, and D. J. Young, "A High-Performance MEMS Capacitive Strain Sensing System", *Journal of Microelectromechanical Systems*, vol. 15, no. 5, Oct. 2006.
- [14] J. Li, L.P. Jon, T. Szymon, G. Andrew, and S. Sanjay, "Interdigital capacitive strain gauges fabricated by direct-write thermal spray and ultrafast laser micromachining." *Sensors and Actuators A: Physical*, vol. 133, no. 1, pp. 1-8, 2007.
- [15] Yaghootkar, B., Azimi, S., & Bahreyni, B. (2017). A high-performance piezoelectric vibration sensor. *IEEE Sensors Journal*, vol. 17, no. 13, pp. 4005-4012, 2017.
- [16] C.D. Do, A. Erbes, J. Yan, K. Soga, and A.A. Seshia, "Vacuum packaged low-power resonant MEMS strain sensor.", *Journal of Microelectromechanical Systems*, vol. 25, no. 5, pp. 851-858, 2016.
- [17] F. Cervera, "ASM Ready Reference: Thermal properties of metals", *ASM International*, 2002.
- [18] H. Watanabe, N. Yamada, and M. Okaji, "Linear Thermal Expansion Coefficient of Silicon from 293 to 1000 K", *International Journal of Thermophysics*, vol. 25, No. 1, Jan. 2004.
- [19] G. Murray, "Handbook of Materials Selection for Engineering Applications", *CRC Press*, 1997.
- [20] Watanabe, H., Yamada, N., & Okaji, M. (2004). "Linear thermal expansion coefficient of silicon from 293 to 1000 K", *International journal of thermophysics*, vol. 25, no. 1, pp. 221-236, 2014.
- [21] <https://www.cmc.ca/en/WhatWeOffer/Products/CMC-00200-02990.aspx>.

Cuong Do received the B. B.Sc. degree in electronics and telecommunication from Vietnam National University, Hanoi, in 2004, the M.Eng. degree in electronics from Chungbuk National University, South Korea, in 2007, and the Ph.D. degree in electronics from the Cork Institute of Technology, Ireland, in 2012.

From 2013 to 2017, he was a Research Associate with the University of Cambridge. Since 2019, he has been an Assistant Professor with the College of Engineering and Computer Science, VinUniversity, Hanoi. His research interests include fields of sensors and sensors fusion for healthcare applications.

Ashwin A. Seshia received his BTech in Engineering Physics in 1996 from IIT Bombay, MS and PhD degrees in Electrical Engineering and Computer Sciences from the University of California, Berkeley in 1999 and 2002 respectively, and the MA from the University of Cambridge in 2008. He joined the faculty of the Engineering Department at the University of Cambridge in October 2002 where he is presently a Professor of Microsystems Technology and a Fellow of Queens' College. He is a Fellow of the Institute of Physics, a Fellow of the Institution for Engineering and Technology and a Fellow of the Institute of Electrical and Electronics Engineers. Prof Seshia currently serves on the editorial boards of the IEEE Journal of Microelectromechanical Systems and the IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control, and the Executive Committee of the European Frequency and Time Forum. He received the 2018 IEEE Sensors Technical Achievement Award (Advanced Career - Sensor Systems) "for pioneering contributions to resonant microsystems with application to sub-surface density contrast imaging and energy harvesting systems".