An Effective Backward Filter Pruning Algorithm Using $K_{1,n}$ Bipartite Graph-Based Clustering and the Decreasing Pruning Rate Approach

Kuo-Liang Chung, *Senior Member, IEEE* and Yu-Lun Chang

Abstract—Setting a fixed pruning rate and/or specified threshold for pruning filters in convolutional layers has been widely used to reduce the number of parameters required in the convolutional neural networks (CNN) model. However, it fails to fully prune redundant filters for different layers whose redundant filters vary with layers. To overcome this disadvantage, we propose a new backward filter pruning algorithm using a sorted bipartite graph- and binary search-based (SBGBS-based) clustering and decreasing pruning rate (DPR) approach. We first represent each filter of the last layer by a bipartite graph $K_{1,n}$, with one root mean set and one n -weight set, where n denotes the number of weights in the filter. Next, according to the accuracy loss tolerance, an SBGBS-based clustering method is used to partition all filters into clusters as maximal as possible. Then, for each cluster, we retain the filter corresponding to the bipartite graph with the median root mean among n root means in the cluster, but we discard the other filters in the same cluster. Following the DPR approach, we repeat the above SBGBS-based filtering pruning approach to the backward layer until all layers are processed. Based on the CIFAR-10 and MNIST datasets, the proposed filter pruning algorithm has been deployed into VGG-16, AlexNet, LeNet, and ResNet. With similar accuracy, the thorough experimental results have demonstrated the substantial parameters and floating-point operations reduction merits of our filter pruning algorithm relative to the existing filter pruning methods.

Index Terms—Backward filter pruning, Bipartite graph $K_{1,n}$, Clustering, Convolutional neural networks (CNN), Decreasing pruning rate, Model compression.

I. INTRODUCTION

Convolutional neural networks (CNN) have been widely used in the design of deep learning models for many applications in computer vision, image processing, compression, speech processing, medical diagnosis, and so on. Due to the great technology achievement in graphics processor units (GPU), several successful CNN models, such as VGG-16 (Visual Geometry Group-16) [29], AlexNet [21], LeNet [23], ResNet [13], and others [2], [31], [8], [12], [28], [19] have been developed. Because of requiring a large number of parameters, they often fail to be deployed in the resource constrained embedded systems for surveillance systems, mobile phones [3], and others.

This work was supported by the contracts MOST-107-2221-E-011-108-MY3 and MOST-108-2221-E-011-077-MY3.

K.L. Chung (Corresponding author. Email: klchung01@gmail.com) and Y.L. Chang are with the Department of Computer Science and Information Engineering, National Taiwan University of Science and Technology, No. 43, Section 4, Keelung Rd., Taipei, 10672, Taiwan.

Therefore, researchers are putting effort into compressing CNN models such that with similar accuracy, the number of parameters and the number of floating-point operations (FLOPs) can be reduced. Here, the parameters and FLOPs reduction ratios denote the ratios of the number of parameters and the number of FLOPs required in one compressed CNN model over that of the original CNN model. The developed model compression methods can be roughly partitioned into four categories, namely the weight pruning approach, the knowledge distillation approach, the low-rank matrix factorization approach, and the filter pruning approach.

In the weight pruning approach [11], [15], when one absolute weight value is less than the specified threshold, it could be zeroized. However, due to the irregular weight zeroization for each filter, it may need a sparse matrix computation-supporting library to accelerate the related convolutional operations. Alternatively, with the help of a lookup table and the special hardware consideration, each weight value could be quantized by limited precision [10], [33].

Hinton *et al.* [18] proposed the knowledge distillation approach to compress the CNN models; their approach learns a small student model via a large teacher model. Readers can read the survey paper [9] for details. The low-rank factorization approach [5], [6], [22], [30] was proposed to decompose the weight matrix as a product of smaller matrices by controlling the rank of the weight matrix such that many parameter values can be predicted, and then those redundant parameter values can be pruned.

Due to user accessibility and friendly tuning, the filter pruning approach provides the efficiency benefit to both CPU and GPU. The related filter pruning works are introduced below.

A. Related Works for Filter Pruning

Li *et al.* [24] proposed a fixed pruning rate and backward filter pruning (FPBFP) method, based on CIFAR-10 [20] and VGG-16. For each layer, they sorted all filters according to their absolute weight sums in increasing order. Next, based on a fixed filter pruning rate, they discarded those filters with smaller absolute weight sums. According to a specified pruning rate for each layer, He *et al.* [17] considered the distortion between the original feature map and the resultant feature map caused by pruning filters. Next, they derived a 1-norm [4] regularization formula to model the filter pruning problem as a constraint minimization problem.

Luo *et al.* [26] first calculated the absolute sum of all entries of each channel in the feature map produced by the i th convolutional layer, and then they pruned the channel with the minimal sum. The channel pruning process is repeated until the specified channel pruning rate is reached, and then the subsequent removal of the corresponding filters in the i th and $(i+1)$ th layers is followed. Ayinde and Zurada [1] proposed a cosine-based merging (CM) method to partition all filters of each layer into a set of clusters based on a specified threshold. Then, for each cluster, they randomly select one filter to represent that cluster and discard the remaining filters in that cluster. The CM method is repeated until all layers have been processed. However, in the CM method, the specified threshold for clustering and the randomly selected filter for representing one cluster may influence the filter pruning effect.

He *et al.* [14] proposed a soft filter pruning (SFP) method. For the considered layer, they first sorted all filters according to their 2-norm values. Next, according to a fixed pruning rate, they zeroized these filters with smaller 2-norm values. In the next retraining step, all the retained filters including the zeroized filters were retrained. Finally, they discarded those filters still with zero values. To improve the SFP method, He *et al.* [16] proposed a geometric median-based filter pruning (GMFP) method. For the considered layer, they first calculated the geometric center of all the filters in that layer, where the sum of all distances between each filter and the geometric center is the smallest among that for the other location. Then, following the same pruning rate for all layers, they discarded the filters which are closest to the geometric center.

In Lin *et al.*'s structure sparsity regularization (SSR) method [25], they deployed $L_{2,0}$ -norm and $L_{2,1}$ -norm [36] in the regularizer of the objective function under the structured sparsity constraint and the user-specified pruning rate. Then, they modeled the filter pruning problem as a minimization problem. To find the best tradeoff between the filter pruning and the minimization of the cross entropy loss, they proposed the alternative updating with the Lagrange multipliers method to solve this minimization problem. The experimental results demonstrated the parameters and FLOPs reduction merits of their two variants, called SSR- $L_{2,0}$ and SSR- $L_{2,1}$, for compressing VGG-16, AlexNet, LeNet, and ResNet relative to the other four methods [27], [35], [32], [34]. Because the code of SSR- $L_{2,0}$ and SSR- $L_{2,1}$ is only available for LeNet, the two variants are included in the comparative methods for LeNet.

B. Contributions

In this paper, without the need to set the pruning rate and/or the specified threshold for each layer, we propose a backward filter pruning algorithm using a sorted bipartite graph- and binary search-based (SBGBS-based) clustering and decreasing pruning rate (DPR) approach. The main contributions of this paper are clarified as follows.

First, we represent each filter in the last convolutional layer by a bipartite graph $K_{1,n}$, with one root mean set and one n -weight set, where n denotes the number of weights in each filter, and then based on the representation $K_{1,n}$, we derive an inequality to reduce the computational complexity when dealing with the frequent SBGBS-based clustering

operations. Under the given accuracy loss tolerance, each of the constructed clusters is represented by one filter, which is associated with $K_{1,n}$ whose root mean is the median root mean among the n root means in the same cluster, and then we discard the other filters in the same cluster, achieving a maximal filter pruning effect for the last layer.

Following the DPR rule, we repeat the above SBGBS-based filtering pruning approach to fully prune redundant filters in the backward layer until the redundant filters in all layers are pruned. Based on the CIFAR-10 and MNIST datasets, the proposed filter pruning algorithm has been deployed into the four CNN models, namely VGG-16, AlexNet, LeNet, and ResNet. With similar accuracy, the thorough experimental results have demonstrated the substantial parameters and floating-point operations reduction merits of our filter pruning algorithm relative to the existing methods [24], [1], [14], [16], [27], [25].

The rest of this paper is organized as follows. In Section II, the proposed SBGBS-based clustering approach for pruning filters in the last layer of the CNN model is presented. In Section III, following the DPR rule, the whole backward filtering pruning algorithm using the SBGBS-based clustering approach is presented. In Section IV, the thorough experimental results are illustrated to justify the substantial parameters and FLOPs reduction merits of our filter pruning algorithm. In Section V, some concluding remarks are made.

II. THE PROPOSED SBGBS-BASED APPROACH TO FULLY PRUNE FILTERS IN THE LAST LAYER

We assume the CNN model $\mathbf{M}$ consists of L convolutional layers, namely $Conv_i$ for $1 \leq i \leq L$, where $Conv_1$ and $Conv_L$ denote the first and last layers in $\mathbf{M}$, respectively. In this study, the four CNN models, namely VGG-16, AlexNet, LeNet, and ResNet-20, are considered.

VGG-16 consists of thirteen layers where $Conv_1$ contains 64 filters, each filter with size $3 \times 3 \times 3$; $Conv_2$ and $Conv_3$ contain 64 and 128 filters, respectively, each filter with size $3 \times 3 \times 64$. $Conv_4$ and $Conv_5$ contain 128 and 256 filters, respectively, each filter with size $3 \times 3 \times 128$. $Conv_6$, $Conv_7$, and $Conv_8$ contain 256, 256, and 512 filters, respectively, each filter with size $3 \times 3 \times 256$. In $Conv_9$ – $Conv_{13}$, each layer contains 512 filters, each filter with size $3 \times 3 \times 512$. AlexNet consists of five layers where $Conv_1$ contains 96 filters, each filter with size $11 \times 11 \times 3$; $Conv_2$ contains 256 filters, each filter with size $5 \times 5 \times 96$; $Conv_3$ contains 384 filters, each filter with size $3 \times 3 \times 256$; $Conv_4$ and $Conv_5$ contain 384 and 256 filters, respectively, each filter with size $3 \times 3 \times 384$.

LeNet consists of only two convolutional layers, namely $Conv_1$ and $Conv_2$, where $Conv_1$ contains 20 filters, each filter with size $5 \times 5 \times 1$; $Conv_2$ contains 50 filters, each filter with size $5 \times 5 \times 20$. Because LeNet consists of only two convolutional layers, usually the fully connected layer, namely FC_1 which contains 500 filters, with each filter comprising $7 \times 7 \times 50$ weights, is included in the filter pruning effect evaluation.

In ResNet-20, there are 19 convolutional layers. To explain how our filter pruning algorithm works for ResNet-20, as depicted in Fig. 1, we partition ResNet-20 into the

first convolutional layer, namely $Conv_1$, and the three macro blocks (MBs), namely MB_1 , MB_2 , and MB_3 . Each macro block MB_i , $1 \leq i \leq 3$, contains three residual blocks, namely $RB_{(i,1)}$, $RB_{(i,2)}$, and $RB_{(i,3)}$. Each residual block $RB_{(i,j)}$, $1 \leq j \leq 3$, consists of two convolutional layers, namely $Conv_{(i+1,j,1)}$ and $Conv_{(i+1,j,2)}$. In ResNet-20, each of $Conv_{(4,j,1)}$ and $Conv_{(4,j,2)}$, $1 \leq j \leq 3$, contains 64 filters, with each filter comprising 3×3 weights; each of $Conv_{(3,j,1)}$ and $Conv_{(3,j,2)}$, $1 \leq j \leq 3$, contains 32 filters, with each filter comprising 3×3 weights.

Fig. 1 The ResNet-20 configuration.

In this section, a new SBGBS-based clustering approach is proposed for fully pruning filters in the last convolutional layer for VGG-16, AlexNet, and LeNet. In Subsection II.D.2, the proposed SBGBS-based clustering approach is also applied to prune filters in the last macro block for ResNet-20.

A. Constructing the Sorted Bipartite Graphs for All Filters in the Last Layer

Initially we assume that the CNN model $\mathbf{M}$ has been trained as the baseline, and assume its recognition accuracy is $\alpha\%$. That is, all weights of filters in $\mathbf{M}$ have been trained. Let the accuracy loss tolerance be denoted by $\delta\%$. Since our filter pruning algorithm follows the backward order, we thus consider filter pruning for the last layer in $\mathbf{M}$. Suppose the last layer $Conv_L$ contains m filters, namely $F[1]$, $F[2]$, ..., and $F[m]$, where each filter $F[i]$, $1 \leq i \leq m$, is of size n and the n weights in $F[i]$ are denoted by $F_1[i]$, $F_2[i]$, ..., and $F_n[i]$. For example, the last layer in VGG-16, namely $Conv_{13}$, contains 512 filters, $F[1]$, $F[2]$, ..., and $F[512]$, and each filter $F[i]$, $1 \leq i \leq 512$, consists of 4608 ($= 3 \times 3 \times 512$) weights, namely $F_1[i]$, $F_2[i]$, ..., and $F_{4608}[i]$.

In $Conv_L$, the n weights of the i th filter $F[i]$, namely $F_1[i]$, $F_2[i]$, ..., and $F_n[i]$, form an n -weight set, as depicted in Fig. 2(a); the mean value of these n weights forms the root mean set. The root mean set and the n -weight set constitute a bipartite graph $K_{1,n}[i]$ ($= G(\mathbf{V}, \mathbf{E})$) for each filter $F[i]$, as depicted in Fig. 2(b), where the node set $\mathbf{V}$ comprises two node sets, namely the root mean set and the n -weight set; the edge set $\mathbf{E}$ contains n edges, with each edge assigning the weight value $\frac{1}{n}$. Based on these constructed m bipartite graphs, namely $K_{1,n}[1]$, $K_{1,n}[2]$, and $K_{1,n}[m]$, we sort these bipartite graphs in increasing order based on their root means.

As depicted in Fig. 2(c), the sorted m bipartite graphs are denoted by $K_{1,n}[S[1]]$, $K_{1,n}[S[2]]$, ..., and $K_{1,n}[S[m]]$, where the index i in $S[i]$ is used to store the sorted order of the bipartite graph $K_{1,n}[S[i]]$ corresponding to the filter $F[S[i]]$. From Fig. 2(c), it yields $S[1] = 5$, $S[2] = 7$, $S[20] = m$, $S[21] = 1$, and $S[m] = 2$, indicating that the sorted orders of the bipartite graphs $K_{1,n}[S[1]]$ ($= K_{1,n}[5]$), $K_{1,n}[S[2]]$ ($= K_{1,n}[7]$), $K_{1,n}[S[20]]$ ($= K_{1,n}[m]$), $K_{1,n}[S[21]]$ ($= K_{1,n}[1]$), and $K_{1,n}[S[m]]$ ($= K_{1,n}[2]$) are 1, 2, 20, 21, and m , respectively. On the other hand, the root mean of the bipartite graph $K_{1,n}[5]$ corresponding to the filter $F[5]$ is the smallest, and the sorted order of $K_{1,n}[5]$ is 1. On the contrary, the root mean of $K_{1,n}[2]$ corresponding to $F[2]$ is the largest, and the sorted order of $K_{1,n}[2]$ is m .

B. Fast Bipartite Graph-Based Closest Filter Finding

In our SBGBS-based clustering approach to prune filters for the last convolutional layer $Conv_L$, given one filter $F[i]$, $1 \leq i \leq m$, finding its closest filter in the considered filter set, denoted by $\mathbf{S}$, is frequently used. We now propose a fast bipartite graph-based closest filter finding method to prune unnecessary 2-norm calculation between the given filter $F[i]$ and the candidate closest filter $F[j]$ ($\in \mathbf{S}$).

The 2-norm distance between $F[i]$ and $F[j]$ is expressed as

$$d(F[i], F[j]) = \sqrt{\sum_{k=1}^n (F_k[i] - F_k[j])^2} = \sqrt{\sum_{k=1}^n (x_k)^2} \quad (1)$$

where $x_k = F_k[i] - F_k[j]$ for $1 \leq k \leq n$. Let $\frac{1}{n} \sum_{k=1}^n (x_k)$ indicate the average value of x_1 , x_2 , ..., and x_n . Suppose the two bipartite graphs, $K_{1,n}[i]$ and $K_{1,n}[j]$, have been

Fig. 2 The sorted bipartite graphs for representing all filters in the last layer with m filters. (a) The n -weight set of the filter $F[i]$ with n weights. (b) The constructed bipartite graph $K_{1,n}[i]$ for the filter $F[i]$. (c) The sorted bipartite graphs for the last layer.

constructed for the two filters $F[i]$ and $F[j]$, respectively. We now prove that the following theorem is true, and the derived inequality in the theorem can be used to terminate the unnecessary computations in the 2-norm calculation between the query filter $F[i]$ and the candidate closest filter $F[j]$, leading to the speedup of the closest filter finding for $F[i]$. After Theorem 1, we take an example to explain how Theorem 1 works to accelerate the closest filter finding for $F[i]$.

Theorem 1. The inequality ' $\sqrt{n} \frac{1}{n} \sum_{k=1}^n (x_k) \leq d(F[i], F[j])$ ' holds.

Proof.

Before proving the above theorem by mathematical induction, we take the square operation on both sides of the above inequality. We thus want to prove that it is true for the following inequality:

$$n \times \left(\frac{\sum_{k=1}^n x_k}{n} \right)^2 \leq d^2(F[i], F[j]) \quad (2)$$

First, we verify the correctness of the basic inequality: $2 \times \left(\frac{x_1 + x_2}{2} \right)^2 \leq x_1^2 + x_2^2$, which can be expressed as $(x_1 + x_2)^2 \leq 2 \times (x_1^2 + x_2^2)$, and further, it can be simplified as $0 \leq (x_1 - x_2)^2$. We complete the correctness verification for this basic inequality.

Assume the inequality in Eq. (2) is true. By induction, we want to prove that the following inequality in Eq. (3) is also true.

$$(n+1) \times \left(\frac{x_1 + x_2 + \dots + x_{n+1}}{n+1} \right)^2 \leq (x_1^2 + x_2^2 + \dots + x_{n+1}^2) \quad (3)$$

Eq. (3) can be expressed as

$$(x_1 + x_2 + \dots + x_{n+1})^2 \leq (n+1) \times (x_1^2 + x_2^2 + \dots + x_{n+1}^2) \quad (4)$$

Let $X = (x_1 + x_2 + \dots + x_n)$. Eq. (4) is expressed as

$$(X + x_{n+1})^2 \leq (n+1) \times (x_1^2 + x_2^2 + \dots + x_{n+1}^2) \quad (5)$$

Expanding both sides of Eq. (5), it yields

$$X^2 + 2 \times X \times x_{n+1} + x_{n+1}^2 \leq n(x_1^2 + x_2^2 + \dots + x_{n+1}^2) + (x_1^2 + x_2^2 + \dots + x_{n+1}^2) \quad (6)$$

From the assumption 'Theorem 1 is true for n ', it yields $X^2 \leq n(x_1^2 + x_2^2 + \dots + x_n^2)$, and Eq. (6) is simplified as

$$2 \times X \times x_{n+1} + x_{n+1}^2 \leq n(x_{n+1}^2) + (x_1^2 + x_2^2 + \dots + x_{n+1}^2) \quad (7)$$

Further, Eq. (7) is simplified as

$$2 \times X \times x_{n+1} \leq n(x_{n+1}^2) + (x_1^2 + x_2^2 + \dots + x_n^2) \quad (8)$$

The left side of Eq. (8) equals $2 \times x_1 \times x_{n+1} + 2 \times x_2 \times x_{n+1} + \dots + 2 \times x_n \times x_{n+1}$ and the right side of Eq. (8) equals $(x_1^2 + x_2^2 + \dots + x_n^2) + (x_{n+1}^2)$. Utilizing the inequality: $2 \times a \times b \leq a^2 + b^2$, we prove that Eq. (8) is true. We thus complete the proof. Q.E.D.

We take an example to explain why the inequality in Theorem 1 can speed up the closest filter finding operation.

Given a filter $F[i]$ corresponding to the bipartite graph $K_{1,n}[i]$, we now want to query the closest filter from the considered filter set, namely $S = \{F[j], F[k], F[l]\}$ where the three filters $F[i]$, $F[j]$, and $F[k]$ are corresponding to $K_{1,n}[j]$, $K_{1,n}[k]$, and $K_{1,n}[l]$, respectively. First, the three bipartite graphs, $K_{1,n}[j]$, $K_{1,n}[k]$, and $K_{1,n}[l]$, are sorted based on their root mean values in increasing order. Suppose

the sorted bipartite graphs are $K_{1,n}[k]$, $K_{1,n}[l]$, and $K_{1,n}[j]$, where $K_{1,n}[l]$ has the median root mean among the three root means. Therefore, by Eq. (1), we compute the exact 2-norm distance between $F[i]$ and $F[l]$, and the value of $d(F[i], F[l])$ is saved as d_{min} .

As defined before, we know $x_k = F_k[i] - F_k[j]$ for $1 \leq k \leq n$. First, we take $O(1)$ time to calculate the mean difference value by subtracting the root mean value of $K_{1,n}[i]$ from the root mean value of $K_{1,n}[j]$. In fact, the calculated mean difference value equals the value of $\frac{\sum_{k=1}^n (x_k)}{n}$. Then, we take $O(1)$ time to calculate the product of $\sqrt{n}$ and the mean difference value, and the product value P equals $\sqrt{n} * \frac{\sum_{k=1}^n (x_k)}{n}$. Suppose the product value P is larger than d_{min} . By Theorem 1, it indicates that the value of $d(F[i], F[j])$ is definitely larger than or equal to P , implying that $d(F[i], F[j])$ is larger than $d(F[i], F[l])$, although we do not really calculate the value of $d(F[i], F[j])$ anymore. Therefore, instead of taking $O(n)$ time to calculate $d(F[i], F[j])$, we only take $O(1)$ time to kick out the filter $F[j]$ as the candidate closest filter. In the same way, we apply Theorem 1 to check whether the filter $F[l]$ can be replaced by $F[k]$ as the closest filter of $F[i]$ quickly.

In general, given a filter $F[i]$ as a key, in the considered filter set $\mathbf{S}$, we can apply Theorem 1 to accelerate the closest filter finding for $F[i]$.

C. The Proposed SBGBS-based Clustering Approach to Fully Prune Filters in the Last Layer

According to the accuracy lower bound $(\alpha - \delta)\%$, an SBGBS-based clustering approach is proposed to fully prune redundant filters in the last layer of the CNN model $\mathbf{M}$, namely $Conv_L$. As defined before, the last layer $Conv_L$ consists of m filters and each filter $F[i]$, $1 \leq i \leq m$, contains n weights, $F_1[i]$, $F_2[i]$, ..., and $F_n[i]$. As depicted in Fig. 2(c), the sorted m bipartite graphs are denoted by $K_{1,n}[S[1]]$, $K_{1,n}[S[2]]$, ..., and $K_{1,n}[S[m]]$.

Based on the m root means of these sorted bipartite graphs, in the first step of the binary search, we select $m * 50\%$ bipartite graphs, namely $K_{1,n}[S[1]]$, $K_{1,n}[S[3]]$, $K_{1,n}[S[5]]$, ..., and $K_{1,n}[S[m]]$, as the initial $m * 50\%$ clusters which are saved in the current cluster set $\mathbf{C}$ with $|\mathbf{C}| = m * 50\%$. Further, we put the unselected $m * 50\%$ bipartite graphs into the remaining filter set, namely $\mathbf{R}$.

We pick up the first bipartite graph in the remaining filter set $\mathbf{R}$ as a key, namely $K_{1,n}[S[2]]$, and then we apply the proposed fast bipartite graph-based closest filter finding operation, which has been presented in the last subsection, to find the closest filter of $F[S[2]]$ from the cluster set $\mathbf{C}$. Suppose the closest filter of $F[S[2]]$ is $F[i']$ ($\in \mathbf{C}$), and then we assign the filter $F[S[2]]$ to the cluster that $F[i']$ belongs to. In the same argument, we repeat the above closest filter finding operation to find the closest filter of $F[S[4]]$ from the current cluster set $\mathbf{C}$, and then we assign the filter $F[S[4]]$ to the cluster that the closest filter of $F[S[4]]$ belongs to. For each filter in the remaining filter set $\mathbf{R}$, after finding its closest filter in the current cluster set $\mathbf{C}$, the updated $m * 50\%$ clusters are still denoted by C_1 , C_2 , ..., and $C_{m*50\%}$, and the union of

C_1 , C_2 , ..., and $C_{m*50\%}$ equals the union of all m filters in the last convolutional layer $Conv_L$, namely $F[1]$, $F[2]$, ..., and $F[m]$.

For each cluster C_i with $|C_i|$ filters, $1 \leq i \leq m * 50\%$, the cluster is represented by the representative filter whose root mean of its bipartite graph is the median root mean among those of all bipartite graphs in the cluster C_i . On the other hand, the representative filter of the cluster C_i is retained, but the remaining $(|C_i| - 1)$ filters in C_i are pruned. After retaining these $m * 50\%$ representative filters, we prune those $m * (1 - 50\%)$ redundant filters in the last layer. In the next retraining step, all the retained filters in the last layer and all filters in the first $(L - 1)$ convolutional layers are retrained.

After retraining the CNN model, if the accuracy decay is larger than the accuracy loss tolerance $\delta\%$, we try the next SBGBS-based iteration and reselect the $m * 25\%$ bipartite graphs from the sorted m bipartite graphs of the last layer $Conv_L$, namely $K_{1,n}[S[1]]$, $K_{1,n}[S[5]]$, $K_{1,n}[S[9]]$, ..., and $K_{1,n}[S[m]]$, as the initial $m * 25\%$ clusters, stored in the current cluster set $\mathbf{C}$. In addition, we put the unselected $m * 75\%$ bipartite graphs into the remaining set, namely $\mathbf{R}$. Otherwise, we select $m * 75\%$ bipartite graphs from the sorted m bipartite graphs of the last layer as the initial $m * 75\%$ clusters which are saved in the current cluster set $\mathbf{C}$. In addition, we put the unselected $m * 25\%$ bipartite graphs into the remaining set $\mathbf{R}$.

In the same way, we repeat the above SBGBS-based clustering approach until the termination condition is reached, maximizing the filter pruning rate for the last layer. Here, the termination condition considers the allowable accuracy loss tolerance and the pruning rate change between two consecutive iterations, and the detailed termination condition will be presented in the proposed whole filter pruning algorithm, called **Algorithm 1**, in Section III.

D. Application to Prune Filters in the Last Layer for VGG16, AlexNet, and LeNet or in the Last Macro Block for ResNet-20

1) *Prune filters in the last layer for VGG-16, AlexNet, and LeNet*: Because the last convolutional layer in VGG-16 and AlexNet is a single layer, the proposed SBGBS-based clustering operation, as described in the last subsection, can be directly applied to fully prune the redundant filters in the last layer for them. Similarly, because the last layer in LeNet, namely the fully connected layer FC_1 , is also a single layer, our SBGBS-based clustering approach can be directly applied to fully prune the redundant filters in the last layer for LeNet.

2) *Prune filters in the last macro block for ResNet-20*: Due to the special input and output connections in the residual blocks of the last macro block in ResNet-20, applying the proposed SBGBS-based clustering approach to prune filters in the last macro block, namely MB_3 , needs a little special treatment. In the last macro block MB_3 , we first apply the proposed SBGBS-based clustering approach to fully prune filters in the three convolution layers, namely $Conv_{(4,3,2)}$, $Conv_{(4,2,2)}$, and $Conv_{(4,1,2)}$, simultaneously, where the pruning rates of the three layers are the same under the accuracy loss tolerance $\delta\%$. Suppose the maximal pruning rate of each layer in $Conv_{(4,3,2)}$, $Conv_{(4,2,2)}$, and $Conv_{(4,1,2)}$ equals $R_{(3,*,2)}$.

In the next retraining step, all retained filters in $Conv_{(4,3,2)}$, $Conv_{(4,2,2)}$, and $Conv_{(4,1,2)}$ in the last macro block MB_3 and the unpruned filters in the other layers are retrained. Further, under the accuracy loss tolerance $\delta\%$ and the DPR rule, we apply the proposed SBGBS-based clustering approach to prune filters backward for $Conv_{(4,3,1)}$, $Conv_{(4,2,1)}$, and $Conv_{(4,1,1)}$ one by one. The pruning rates of $Conv_{(4,3,1)}$, $Conv_{(4,2,1)}$, and $Conv_{(4,1,1)}$, namely $R_{(3,1,1)}$, $R_{(3,2,1)}$, and $R_{(3,3,1)}$, respectively, must be less than or equal to $R_{(3,*,2)}$ and follow the DPR rule: $R_{(3,1,1)} \leq R_{(3,2,1)} \leq R_{(3,3,1)}$. As a result, the pruning rate $R_{3,1,1}$ is used as the pruning rate upper bound for pruning filters in the backward macro block, namely MB_2 .

III. THE PROPOSED BACKWARD SBGBS-BASED FILTER PRUNING ALGORITHM USING THE DPR RULE

After pruning the last convolutional layer (or the last macro block) of the CNN model $\mathbf{M}$, namely $Conv_L$ (or $MB_{L'}$), using our SBGBS-based clustering approach, suppose the pruning rates of $Conv_L$ and $MB_{L'}$ are R_L and $R_{L'}$, respectively. Taking R_L and $R_{L'}$ as the pruning rate upper bounds for the $(L-1)$ th convolutional layer $Conv_{L-1}$ and the $(L'-1)$ th macro block $MB_{L'-1}$, respectively, we proceed to prune the redundant filters in $Conv_{L-1}$ and $MB_{L'-1}$. According to the DPR rule, the proposed SBGBS-based clustering approach is further applied to fully prune filters for $Conv_{L-1}$ and $MB_{L'-1}$ until all the convolutional layers are processed. For simplicity, in the description of our backward SBGBS-based filter pruning

algorithm, the two notations ' $Conv_i$ ' and ' MB_i ' are briefly denoted as ' $Conv_i$ ' without confusion. The whole backward filter pruning algorithm for all layers using the SBGBS-based clustering approach and the DPR rule is listed below.

IV. EXPERIMENTAL RESULTS

Based on the CIFAR-10 dataset for VGG-16, AlexNet, and ResNet, the comprehensive experiments have been carried out to demonstrate the parameters and FLOPs reduction merits of our filter pruning method relative to the existing state-of-the-art filter pruning methods [24], [1], [14], [16]. Based on the MNIST dataset, the comprehensive experimental results have also demonstrated the parameters and FLOPs reduction merits of our method relative to the methods [27], [25].

All experiments are implemented using a desktop with an Intel Core i7-7700 CPU running at 3.6 GHz with 32 GB RAM and a Nvidia 2080Ti GPU. The operating system is Microsoft Windows 10 64-bit. The source code of our filter pruning algorithm is implemented by Python language and can be accessed from [7].

Following the order: VGG-16, AlexNet, LeNet, and ResNet-20, the parameters and FLOPs reduction merits of our filter pruning method are illustrated one at a time when compared with the comparative filter pruning methods.

A. The Parameters and FLOPs Reduction Merits for VGG-16

Table I lists the parameters and FLOPs reduction ratios merits of our filter pruning method, abbreviated as 'Ours',

Algorithm 1 SBGBS-based backward filter pruning for a CNN model $\mathbf{M}$ with $\mathbf{L}$ layers

Input: Trained CNN model $\mathbf{M}$ with accuracy $\alpha\%$ as a baseline and the allowable accuracy loss tolerance $\delta\%$.

Output: Compressed CNN model $\mathbf{M}$.

Step 1. Perform $k := \mathbf{L}$, $R_{upper}^{(\mathbf{L})} := 1$, $R_{lower}^{(\mathbf{L})} := 0$, and $R^{(\mathbf{L})} := 0$. /* (**initialization**) $R^{(\mathbf{L})}$ denotes the initial pruning rate for the L th layer */

Step 2. Construct the sorted bipartite graphs for all filters, denoted by the set $\mathbf{F}^{(k)}$, in the k th layer.

Step 3. /* (**iterative SBGBS-based filter pruning**) */

Perform $R_{old}^{(k)} := R^{(k)}$ and $R^{(k)} := \frac{R_{upper}^{(k)} + R_{lower}^{(k)}}{2}$.

If $(|R_{old}^{(k)} - R^{(k)}| \geq 0.0125)$ /* maximal times = 6 as one termination condition */

then

{Perform the SBGBS-based filter pruning method on $\mathbf{F}^{(k)}$ to obtain the $|\mathbf{F}^{(k)}|(1 - R^{(k)})$ representative filters, and these representative filters are saved in $\mathbf{F}^{(k)}$. Retrain the CNN model $\mathbf{M}$ based on $\mathbf{F}^{(k)}$ in the k th layer and the stationary filters in the other layers.

If (the accuracy of the trained model $\mathbf{M} > (\alpha - \delta)\%$)

then

{Perform $R_{lower}^{(k)} := \frac{R_{upper}^{(k)} + R_{lower}^{(k)}}{2}$. /* move the binary search cursor to the right */
Go to Step 3.}

else

Perform $R_{upper}^{(k)} := \frac{R_{upper}^{(k)} + R_{lower}^{(k)}}{2}$. /* move the binary search cursor to the left */}

Step 4. /*(**termination test**)*/

If $(k = 1)$

then

Report the compressed model $\mathbf{M}$ as the output and stop **Algorithm 1**.

else

{Perform $R_{upper}^{(k-1)} := R^{(k)}$, $R_{lower}^{(k-1)} := 0$, $R^{(k-1)} := R^{(k)}$, and $k := k - 1$.

Go to Step 2. /* go to the backward layer */}

Table. I

THE PARAMETERS AND FLOPS REDUCTION MERITS OF THE PROPOSED METHOD FOR VGG-16.

Method	#(Parameters)	Parameters Reduction Rate	#(FLOPs)	FLOPs Reduction Rate	Accuracy	Accuracy loss
Baseline	14.90M	0%	626.90M	0%	91.60%	0%
FPBFP [24]	5.36M	64.00%	412.5M	34.20%	91.53%	0.07%
CM [1]	5.41M	63.68%	350.8M	44.05%	91.56%	0.04%
SFP [14]	8.37M	43.80%	353.3M	43.65%	91.55%	0.05%
GMFP [16]	7.39M	50.41%	310.2M	50.52%	91.55%	0.05%
Ours	1.74M	88.35%	301M	51.98%	91.57%	0.03%

Table. II

THE FILTER PRUNING RATE OF EACH CONVOLUTIONAL LAYER FOR VGG-16.

Purning Rate (Layer)	13	12	11	10	9	8	7	6	5	4	3	2	1
FPBFP [24]	50%	50%	50%	50%	50%	50%	0%	0%	0%	0%	0%	0%	50%
CM [1]	60.55%	60.35%	67.18%	62.11%	27.73%	16.99%	4.69%	3.91%	13.67%	11.72%	43.75%	53.13%	0%
SFP [14]	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%	25%
GMFP [16]	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%	30%
Ours	87.5%	87.5%	87.5%	87.5%	62.5%	62.5%	50.5625%	31.25%	31.25%	0%	0%	0%	0%

Table. III

THE PARAMETERS AND FLOPS REDUCTION MERITS OF THE PROPOSED METHOD FOR ALEXNET.

Method	#(Parameters)	Parameters Reduction Ratio	#(FLOPs)	FLOPs Reduction Ratio	Accuracy	Accuracy loss
Baseline	24.78M	0%	291.13M	0%	78.77%	0%
CM [1]	23.32M	5.89%	181.61M	37.62%	78.75%	0.02%
SFP [14]	21.92M	11.56%	188.04M	35.41%	78.75%	0.02%
Ours	20.52M	17.19%	138.55M	52.41%	78.82%	-0.05%

Table. IV

THE FILTER PRUNING RATE OF EACH CONVOLUTIONAL LAYER FOR ALEXNET.

Purning Rate (Layer)	5	4	3	2	1
CM [1]	12.89%	7.55%	2.34%	19.92%	57.29%
SFP [14]	27%	27%	27%	27%	27%
Ours	42.19%	42.19%	42.19%	42.19%	42.19%

Table. V

THE PARAMETERS AND FLOPS REDUCTION MERITS OF THE PROPOSED METHOD FOR LENET.

Method	#(Parameters)	Parameters Reduction Ratio	#(FLOPs)	FLOPs Reduction Ratio	Accuracy	Accuracy loss
Baseline	1256.08K	0%	13.04M	0%	99.25%	0%
TE [27]	101.49K	91.92%	0.83M	93.65%	99.23%	0.02%
SSR-L _{2,0} [25]	81.77K	93.49%	0.53M	95.96%	99.21%	0.04%
SSR-L _{2,1} [25]	61.30K	95.12%	0.67M	94.87%	99.21%	0.04%
Ours	39.19K	96.88%	0.66M	94.91%	99.23%	0.02%

Table. VI

THE FILTER PRUNING RATE OF EACH CONVOLUTIONAL LAYER FOR LENET.

Purning Rate (Layer)	FC ₁	Conv ₂	Conv ₁
TE [27]	74.6%	76%	90%
SSR-L _{2,0} [25]	70.4%	78%	90%
SSR-L _{2,1} [25]	78.4%	78%	85%
Ours	75%	87.5%	70%

Table. VII
THE PARAMETERS AND FLOPS REDUCTION MERITS OF THE PROPOSED METHOD FOR RESNET-20.

Method	#(Parameters)	Parameters Reduction Ratio	#(FLOPs)	FLOPs Reduction Ratio	Accuracy	Accuracy loss
Baseline	270.90K	0%	81.63M	0%	92.02%	0%
CM [1]	139.11K	48.65%	36.39M	55.42%	90.23%	1.79%
SFP (30%) [14]	136.75K	49.52%	47.18M	42.20%	90.83%	1.19%
SFP (40%) [14]	102.51K	62.16%	37.55M	54.00%	90.33%	1.69%
GMFP (40%) [16]	152.51K	62.16%	37.55M	54.00%	90.48%	1.54%
Ours	75.88K	71.99%	35.34M	56.71%	90.53%	1.49%

Table. VIII
THE FILTER PRUNING RATE OF EACH CONVOLUTIONAL LAYER FOR RESNET-20.

Purning Rate (Layer)	19	18	17	16	15	14	13	12	11
CM [1]	42.19%	15.63%	42.19%	12.5%	42.19%	17.19%	15.63%	18.75%	15.63%
SFP (30%) [14]	30%	30%	30%	30%	30%	30%	30%	30%	30%
SFP (40%) [14]	40%	40%	40%	40%	40%	40%	40%	40%	40%
GMFP (40%) [16]	40%	40%	40%	40%	40%	40%	40%	40%	40%
Ours	50%	50%	50%	50%	50%	50%	50%	50%	50%

Purning Rate (Layer)	10	9	8	7	6	5	4	3	2	1
CM [1]	25%	15.63%	43.75%	50%	50%	50%	50%	50%	50%	50%
SFP [14]	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%
GMFP [16]	40%	40%	40%	40%	40%	40%	40%	40%	40%	40%
Ours	50%	50%	50%	25%	0%	25%	0%	25%	0%	25%

relative to the four methods [1], [14], [16], [24]. In Table II, the filter pruning rates of all the convolutional layers follow the original implementation of the four comparative methods.

Table I indicates that by the baseline method without pruning any filters, the number of required parameters, denoted by #(Parameters), the number of required FLOPs, denoted by #(FLOPs), and the accuracy are 14.90M, 626.90M, and 91.60%, respectively. In Table I, with the highest accuracy and the lowest accuracy loss, our filter pruning method has the highest parameters and FLOPs reduction ratios in boldface relative to the four comparative methods. The parameters reduction ratio gains of our method over FPBFP [24], SPF [14], CM [1], and GMFP [16] are 24.35%, 44.55%, 24.67%, and 37.94%, respectively; the FLOPs reduction ratio gains of our method over the four comparative methods are 17.78%, 8.33%, 7.93%, and 1.46%, respectively.

B. The Parameters and FLOPs Reduction Merits for AlexNet

Table III indicates that using the baseline method, the values of #(Parameters), #(FLOPs), and the accuracy are 24.78M, 291.13M, and 78.77%, respectively. In Table III, we observe that the parameters reduction ratio gains of our filter pruning method over the CM method [1] and the SFP method [14] are 11.3% and 5.63%, respectively; the FLOPs reduction ratio gains of our method over the two comparative methods are 14.79% and 17%, respectively. Table IV lists the filter pruning rates of all the convolutional layers following the original implementation of the two comparative methods.

C. The Parameters and FLOPs Reduction Merits for LeNet

For LeNet, based on the MNIST dataset, Table V tabulates the parameters and FLOPs reduction ratios comparison among our filter pruning method and the two comparative methods [27], [25]. Table VI lists the filter pruning rates of FC_1 , $Conv_2$, $Conv_1$ using the considered methods.

Table V indicates that using the baseline method, the values of #(Parameters), #(FLOPs), and the accuracy are 1256.08K, 13.04M, and 99.25%, respectively. When compared with the comparative methods [27], [25], the parameters reduction ratio gains of our method over the TE method [27], the SSR- $L_{2,0}$ method [25], and the SSR- $L_{2,1}$ method [25] are 4.96%, 3.39%, and 1.76%, respectively. The FLOPs reduction ratio gains of our method over the TE method and the SSR- $L_{2,1}$ method are 1.26% and 0.04%, respectively, while the FLOPs reduction ratio gain of our method over SSR- $L_{2,0}$ is -1.05%.

D. The Parameters and FLOPs Reduction Merits for ResNet20

When compared with the three comparative methods, namely the CM method with the specified threshold 0.85 [1], the SFP method with the two pruning rates 30% and 40% [14], abbreviated as SFP (30%) and SFP (40%), respectively, and the GMFP method with the pruning rate 40% [16], abbreviated as GMFP (40%), Table VII demonstrates the parameters and FLOPs reduction ratios merits of our filter pruning method. In the baseline method, the values of #(Parameters), #(FLOPs), and the accuracy are 270.90K, 81.63M, and 92.02%, respectively.

Table VII indicates that the parameters reduction ratio gains of our filter pruning method over CM, SFP (30%), SFP (40%), and GMFP (40%) are 23.34%, 22.47%, 9.83%, 9.83%, respectively; the FLOPs reduction ratio gains of our method

over them are 1.29%, 14.51%, 2.71%, 2.71%, respectively. Although the SFP (30%) method has the highest accuracy, namely 90.83%, its parameters reduction and FLOPs reduction ratios are much worse than ours. Table VIII lists the pruning rate of each convolutional layer using the considered methods.

V. CONCLUSIONS

Without setting fixed pruning rates and/or specifying thresholds, the proposed backward filter pruning algorithm using the SBGBS-based clustering and the DPR approach has been presented. Based on the CIFAR-10 and MNIST datasets and the four CNN models, VGG-16, AlexNet, LeNet, and ResNet, the comprehensive experiments have been carried out to demonstrate the substantial parameters and FLOPs reduction merits of our filter pruning method when compared with the state-of-the-art filter pruning methods [1], [14], [16], [24], [27], [25].

VI. ACKNOWLEDGEMENT

The authors appreciate the proofreading help of Ms. C. Harrington to improve the manuscript.

REFERENCES

- [1] B. O. Ayinde and J. M. Zurada, "Building efficient convnets using redundant feature pruning," *arXiv preprint arXiv:1802.07653*, Feb. 2018.
- [2] V. Badrinarayanan, A. Kendall, and R. Cipolla, "SegNet: A deep convolutional encoder-decoder architecture for image segmentation," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 39, no. 12, pp. 2481-2495, Dec. 2017.
- [3] C. F. Chen, G. G. Lee, V. Sritapan, and C. Y. Lin, "Deep convolutional neural network on iOS mobile devices," *IEEE International Workshop on Signal Processing Systems*, pp. 130-135, Oct. 2016.
- [4] B. N. Datta, "Numerical linear algebra and applications", *Brooks/Cole Publishing Company*, pp. 315-324, 1995.
- [5] M. Denil, B. Shakibi, L. Dinh, M. Ranzato, and N. de Freitas, "Predicting parameters in deep learning," *International Conference on Neural Information Processing Systems*, vol. 2, pp. 2148-2156, Dec. 2013.
- [6] E. L. Denton, W. Zaremba, J. Bruna, Y. LeCun, and R. Fergus, "Exploiting linear structure within convolutional networks for efficient evaluation," *arXiv preprint arXiv:1404.0736*, Apr. 2014.
- [7] *Execution code*. Accessed: 26 Jan. 2019. [Online]. Available: ftp://140.118.175.164/Model_Compression/Codes.
- [8] I. J. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, "Generative adversarial networks," *arXiv preprint arXiv:1406.2661*, Jun. 2014.
- [9] J. Gou, B. Yu, S. J. Maybank, and D. Tao, "Knowledge distillation: A survey," *arXiv preprint arXiv:2006.05525*, Jun. 2021.
- [10] S. Han, H. Mao, and W. J. Dally, "Deep compression: Compressing deep neural networks with pruning, trained quantization and Huffman coding," *arXiv preprint arXiv:1510.00149*, Oct. 2015.
- [11] S. Han, J. Pool, J. Tran, and W. J. Dally, "Learning both weights and connections for efficient neural network," *arXiv preprint arXiv:1506.02626*, Jun. 2015.
- [12] K. He, G. Gkioxari, P. Dollar, and R. Girshick, "Mask r-cnn," *IEEE International Conference on Computer Vision*, pp. 2961-2969, 2017.
- [13] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," *arXiv preprint arXiv:1512.03385*, Dec. 2015.
- [14] Y. He, G. Kang, X. Dong, Y. Fu, and Y. Yang, "Soft filter pruning for accelerating deep convolutional neural networks," *arXiv preprint arXiv:1808.06866*, Aug. 2018.
- [15] Y. He, J. Lin, Z. Liu, H. Wang, L. J. Li, and S. Han, "Amc: Automl for model compression and acceleration on mobile devices," *European Conference on Computer Vision*, pp. 784-800, 2018.
- [16] Y. He, P. Liu, Z. Wang, Z. Hu, and Y. Yang, "Filter pruning via geometric median for deep convolutional neural networks acceleration," *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4340-4349, 2019.
- [17] Y. He, X. Zhang, and J. Sun, "Channel pruning for accelerating very deep neural networks," *IEEE International Conference on Computer Vision*, pp. 1398-1402, Oct. 2017.
- [18] G. E. Hinton, O. Vinyals, and J. Dean, "Distilling the knowledge in a neural network," *NIPS Deep Learning and Representation Learning Workshop*, pp. 1-9, 2015.
- [19] A. G. Howard, M. Zhu, B. Chen, and D. Kalenichenko, "MobileNets: Efficient convolutional neural networks for mobile vision applications," *arXiv preprint arXiv:1704.04861*, Apr. 2017.
- [20] A. Krizhevsky and G. Hinton, "Learning multiple layers of features from tiny images," *Technical Report, Computer Science Department, University of Toronto*, 2009.
- [21] A. Krizhevsky, I. Sutskever, and G. Hinton, "ImageNet classification with deep convolutional neural networks," *Conference on Neural Information Processing Systems*, pp. 1097-1105, 2012.
- [22] V. Lebedev, Y. Ganin, M. Rakhuba, I. Oseledets, and V. Lempitsky, "Speeding-up convolutional neural networks using fine-tuned cp-decomposition," *arXiv preprint arXiv:1412.6553*, Apr. 2015.
- [23] Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner, "Gradient-based learning applied to document recognition," *Proceedings of the IEEE*, vol. 86, no. 11, pp. 2278-2324, Nov. 1998.
- [24] H. Li, A. Kadav, I. Durdanovic, H. Samet, and H. P. Graf, "Pruning filters for efficient convnets," *arXiv preprint arXiv:1608.08710*, Mar. 2017.
- [25] S. Lin, R. Ji, Y. Li, C. Deng, and X. Li, "Toward compact convnets via structure-sparsity regularized filter pruning," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 31, no. 2, pp. 574-588, Feb. 2020.
- [26] J. Luo, J. Wu, and W. Lin, "ThiNet: A filter level pruning method for deep neural network compression," *arXiv preprint arXiv:1707.06342*, Jul. 2017.
- [27] P. Molchanov, S. Tyree, T. Karras, T. Aila, and J. Kautz, "Pruning convolutional neural networks for resource efficient inference," *arXiv preprint arXiv:1611.06440*, Jun. 2017.
- [28] O. Ronneberger, P. Fischer, and T. Brox, "U-net: Convolutional networks for biomedical image segmentation," *International Conference On Medical Image Computing & Computer Assisted Intervention*, vol. 9351, pp. 234-241, 2015.
- [29] K. Simonyan and A. Zisserman, "Very deep convolutional networks for large-scale image recognition," *arXiv preprint arXiv:1409.1556*, Sep. 2014.
- [30] S. Swaminathan, D. Garg, R. Kannan, and F. Andres, "Sparse low rank factorization for deep neural network compression," *Neurocomputing*, vol. 398, pp. 185-196, Jul. 2020.
- [31] C. Szegedy, W. Liu, Y. Jia, P. Sermanet, S. Reed, D. Anguelov, D. Erhan, V. Vanhoucke, and A. Rabinovich, "Going deeper with convolutions," *arXiv preprint arXiv:1409.4842*, Sep. 2014.
- [32] A. Torfı, R. A. Shirvani, S. Soleymani, and N. M. Nasrabadi, "Attention-based guided structured sparsity of deep neural networks," *arXiv preprint arXiv:1802.09902*, Jul. 2018.
- [33] K. Wang, Z. Liu, Y. Lin, J. Lin, and S. Han, "Haq: Hardware-aware automated quantization with mixed precision," *IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8612-8620, 2019.
- [34] W. Wen, C. Wu, Y. Wang, Y. Chen, and H. Li, "Learning structured sparsity in deep neural networks," *In Advances in Neural Information Processing Systems*, pp. 2074-2082, 2016.
- [35] J. Yoon, and S. J. Hwang, "Combined group and exclusive sparsity for deep neural networks," *IET Image Processing*, vol. 13, no. 5, pp. 779-784, May. 2019.
- [36] M. Yuan and Y. Lin, "Model selection and estimation in regression with grouped variables," *J. Roy. Statist. Soc., B (Statist. Methodol.)*, vol. 68, no. 1, pp. 49-67, Dec. 2005.

Kuo-Liang Chung received his B.S., M.S., and Ph.D. degrees from the Computer Science and Information Engineering Department at National Taiwan University, Taipei, Taiwan. He has been one Chair Professor of the Department of Computer Science and Information Engineering at National Taiwan University of Science and Technology, Taipei, Taiwan, since 2009. He was the recipient of the Distinguished Research Award (2004-2007;2019-2022) and Distinguished Research Project Award (2009-2012) from the Ministry of

Science and Technology of R.O.C. He has been the Associate Editor of the Journal of Visual Communication and Image Representation since 2011. His research interests include deep learning, image processing, and video compression.

Yu-Lun Chang received his B.S. degree in Computer Science and Information Engineering from the National Chung Cheng University, Chiayi, R.O.C in 2019. He is currently working towards his M.S. degree in Computer Science and Information Engineering at the National Taiwan University of Science and Technology, Taipei, R.O.C. His research interests include machine learning and model compression.