

Impact of Wireless-Powered Communications in Coexisting Mobile Networks

Luis Irio ¹, Rodolfo Oliveira ², Daniel B. da Costa ², and Mohamed-Slim Alouini ²

¹Instituto de Telecomunicações

²Affiliation not available

October 30, 2023

Impact of Wireless-Powered Communications in Coexisting Mobile Networks

Luis Irio, Rodolfo Oliveira, *Senior Member, IEEE*, Daniel B. da Costa, *Senior Member, IEEE*, and Mohamed-Slim Alouini, *Fellow, IEEE*

Abstract

In this letter, we investigate the impact of wireless-powered communications when energy is harvested from multiple static and/or mobile wireless coexisting networks. In a first step, we characterize the aggregate power received by a harvester node when it harnesses the energy generated by the coexisting wireless networks. Considering that the harvester node acts as a transmitter after the harvesting duration, we derive the outage probability for such coexisting scenario. In addition, the throughput achieved by the harvester node is also characterized, and the optimal harvesting duration is identified taking into account the mobility of the coexisting networks, the features of the static networks, the energy harvesting process, as well as the communication performance between the harvester node and the receiver. Our work shows that the distribution of the power received by the harvester from the coexisting networks can be accurately approximated by an $\alpha - \mu$ distribution. Moreover, the mobility also impacts on the optimal throughput of the wireless-powered communications, which is accurately confirmed by the proposed analysis and extensive simulations.

Index Terms

mobility, coexistence, energy-harvesting, performance evaluation.

I. INTRODUCTION

Wireless-powered communications (WPC) have been recently proposed to extend the network's lifetime. In WPCs, the aggregate energy collected by a harvester node from multiple radio-frequency (RF) signals is used to power the communication process. Coexisting interference

L. Irio, and R. Oliveira are with the Instituto de Telecomunicações, 1049-001 Lisbon, Portugal, and also with the Departamento de Engenharia Electrotécnica, Faculdade de Ciências e Tecnologia, Universidade Nova de Lisboa, 2829-516 Caparica, Portugal (e-mail: l.iri@campus.fct.unl.pt, rado@fct.unl.pt). D. B. da Costa is with the Department of Computer Engineering, Federal University of Ceará, Sobral-CE, Brazil (e-mail: danielbcosta@ieee.org). Mohamed-Slim Alouini is with the King Abdullah University of Science and Technology (KAUST), Thuwal, Saudi Arabia (e-mail: slim.alouini@kaust.edu.sa).

was recently studied in [1] for static networks. The effect of the interference on the performance of energy harvesting systems has been analyzed in [2] and [3]. The interference caused by multiple transmitters was characterized in [4], which considers that different ambient RF energy sources cause interference to a wireless sensor node. The RF energy sources are distributed as a Ginibre α -determinantal point process (DPP), and the performance analysis is stated as a stochastic geometry problem. Most of the existing works do not address large scale WPC networks due to the challenges associated with the characterization of the harvested RF energy in the presence of dominant transmitters. An exception to this is the work in [5], which uses the probability generating functional of a Poisson point process (PPP), to characterize the distribution of the harvested energy.

To the best of the authors' knowledge, the characterization of WPC systems that harvest energy from multiple coexisting networks (including static and/or mobile ones), has not yet been addressed in the literature. In order to fill partly this gap that exists in the literature, this work aims to first study the distribution of the harvested energy from multiple energy sources belonging to different coexisting networks. We consider the case where mobile and/or static networks may coexist together in the same band. Admitting that the harvester node acts as a transmitter after the energy harvesting period, we derive the outage probability for such scenario. In addition, we study the throughput achieved by the harvester node, identifying the optimal energy harvesting time allocation having into account the mobility of the mobile networks, the features of the static networks, the energy harvesting process, as well as the communication performance between the harvester node and the receiver.

The remainder of this paper is organized as follows. Section II introduces the system model adopted in the work. Section III characterizes the energy harvested by a node from different coexisting wireless networks, and Section IV describes the throughput achieved by the harvester node. Finally, Section V assesses the accuracy of the proposed methodology along with insightful discussions.

Notations and functions: $f_X(\cdot)$ and $P(X = x)$ represent the probability density function (PDF) and the probability of a random variable (RV) X , respectively. $\Gamma(\cdot)$ represents the complete Gamma function [6, Eq. (8.310.1)]. $\Gamma(\cdot, \cdot)$ denotes the incomplete Gamma function [6, Eq. (8.350.1)]. $\text{Nakagami}(x_1, x_2)$ denotes the Nakagami distribution with shape x_1 and spread x_2 . $E[X]$ and $\text{Var}[X]$ are the expectation and variance of the RV X , respectively.

II. SYSTEM MODEL

A. Coexisting Wireless Networks

In this work, we consider the scenario illustrated in Fig. 1, where multiple Υ_η networks, with $\eta = 1, \dots, v$, coexist in the same RF band, and same spatial region with area $X_{max} \times Y_{max}$. The v networks can be static or mobile. The nodes of the static networks are deployed according to a homogeneous PPP. The nodes of the mobile networks move according to the Random Waypoint (RWP) mobility model [7], where each node is initially placed in a random position (x, y) sampled from the uniform distributions represented by $x \in [0, X_{max}]$ and $y \in [0, Y_{max}]$, and move to a random ending point with velocity uniformly sampled from $[V_{min}, V_{max}]$. The nodes stop at the ending point for pause time T_p . After reaching the ending point a node repeats the same cycle. The average velocity of the nodes is denoted by $E[V]$, which was studied in [7].




Fig. 1. A harvester node N_{Tx} receives energy from v coexistent networks to transmit information to the node N_{Rx} . The dashed circles represent the boundaries of the annuli considered in the proposed model. The inner circle radius is denoted by $R_{\eta,1}$, and $R_{\eta,L_{\eta}+1}$ denotes the outer circle radius.

For modeling purposes, we adopt the spatial circular model (SCM) considered in [8], where the analysis of the energy received by the harvester node (node N_{Tx} in Fig. 1) from the network Υ_η is derived by considering the nodes located in the L_η annuli centered on the harvester node. The radius of the larger and smaller circles of the annulus $l \in \{1, \dots, L_\eta\}$, are represented by $R_{\eta,l+1} = (R_{\eta,l} + l\rho)$ and $R_{\eta,l}$, respectively, where ρ denotes the annulus' width. The nodes

of a given network Υ_η are thus located in a circular region with area $A_\eta = \sum_{l=1}^{L_\eta} A_{\eta,l}$, where $A_{\eta,l} = \pi((R_{\eta,l+1})^2 - (R_{\eta,l})^2)$ denotes the area of the annulus l .

The number of transmitters of the network Υ_η located in a particular annulus $l \in \{1, \dots, L_\eta\}$ is represented by the RV $X_{\eta,l}$. For both static and mobile networks we consider that $X_{\eta,l}$ is distributed according to a truncated Poisson distribution given by

$$P(X_{\eta,l} = k) = \frac{(\lambda_{\eta,l} A_{\eta,l} \tau_\eta)^k e^{-\lambda_{\eta,l} A_{\eta,l} \tau_\eta}}{k! \sum_{i=0}^{n_\eta} \frac{(\lambda_{\eta,l} A_{\eta,l} \tau_\eta)^i}{i!} e^{-\lambda_{\eta,l} A_{\eta,l} \tau_\eta}}, 0 \leq k \leq n_\eta,$$

where $\lambda_{\eta,l}$ is the node's spatial density, n_η is the total number of nodes of the network Υ_η , and τ_η is the individual transmission probability. We highlight that for static networks $\lambda_{\eta,l}$ is equal for all L_η annulus. However, for RWP mobile networks, the spatial distribution of the nodes is approximated by an inhomogeneous PPP. Consequently, for mobile RWP networks, $\lambda_{\eta,l}$ takes a different value for each annulus l . In this work, we consider that the density parameter $\lambda_{\eta,l}$ adopted to model the mobile RWP networks is computed as proposed in [9, Eq. (8)], which takes into account the annuli's geometry $(\rho; L_\eta; R_{\eta,1})$, and mobility parameters $(V_{min}; V_{max}; X_{max}; Y_{max}; T_p)$.

B. Propagation Effects

The power received by the harvester node (N_{Tx}) from the $n_{\eta,l}$ transmitters of the network Υ_η located in the annulus l is denoted by $I_{\eta,l} = \sum_{i=1}^{n_{\eta,l}} I_{\eta,l,i}$. $I_{\eta,l,i}$ represents the power received from the i -th transmitter, which can be written as follows

$$I_{\eta,l,i} = P_{Tx_\eta} \psi_i (r_{\eta,l})^{-m},$$

where P_{Tx_η} is the transmitted power, ψ_i is the instantaneous value of the fading channel and shadowing gain, $r_{\eta,l}$ is the distance between the i -th transmitter and N_{Tx} , and m denotes the path-loss coefficient. The values ψ_i and $r_{\eta,l}$ represent instantaneous values of the RVs Ψ_i and $R_{\eta,l}$, respectively. Ψ_i represents small-scale fading and shadowing effects. Small-scale fading amplitude is assumed to be Rayleigh distributed with mean power $2\sigma_\zeta^2 = 1$. Lognormal shadowing is also assumed, with mean and standard deviation of the RV's natural logarithm given by $\mu_\xi = -\sigma_\xi^2/2$ and $\sigma_\xi > 0$, respectively. To simplify the composite fading model, we consider that the power of the Rayleigh and Lognormal effects can be jointly approximated by a Gamma distribution [10] with scale and shape parameters given by $\theta_{\psi_i} = \left(\frac{2(\vartheta+1)}{\vartheta} - 1\right) \omega_s$ and $k_{\psi_i} = \frac{1}{\frac{2(\vartheta+1)}{\vartheta} - 1}$, respectively, in which $\vartheta = (e^{\sigma_\xi^2} - 1)^{-1}$ and $\omega_s = e^{\mu_\xi} \sqrt{\frac{\vartheta+1}{\vartheta}}$.

C. Wireless-Powered Communications

We consider a WPC network with a time-switching protocol. In particular, wireless energy transfer is assumed in the downlink (DL) band, where the node N_{Tx} accumulates energy from the transmitters of the v different coexisting wireless networks (Fig. 1). The node N_{Tx} first harvests energy during the time interval cT from the DL RF band, and then uses it to transmit data to N_{Rx} over the uplink (UL) band. The transmission lasts $(1 - c)T$, where T is the total duration of a time-switching cycle and c represents the time splitting factor. We consider an unitary cycle duration, i.e., $T = 1$.

A Rayleigh fading channel between the nodes N_{Tx} and N_{Rx} is considered, and the distance between the nodes is denoted as d_1 . The transmission power for information transfer depends on the energy harvested in the DL band and is denoted by $P_{N_{Tx}}$. Consequently, the signal received by N_{Rx} can be written as

$$y_{N_{Tx}} = \frac{1}{\sqrt{d_1^m}} \sqrt{P_{N_{Tx}}} h_1 x_c + n_d, \quad (1)$$

where h_1 is the channel coefficient from the transmitter N_{Tx} to the receiver N_{Rx} , x_c is the normalized information signal transmitted by N_{Tx} , and n_d is the zero-mean additive white Gaussian noise (AWGN) at the receiver.

III. HARVESTED ENERGY

In this section, we derive the energy harvested by the node N_{Tx} from the v coexisting networks. Specifically, we describe how the aggregate power received by N_{Tx} from all transmitters of the v coexisting networks can be approximated by an α - μ distribution. Then, the aggregate power is used to derive the energy harvested during the harvesting period cT .

The work in [11] has proved that the aggregate power received from multiple nodes located over a single circle of a homogenous Poisson network is distributed according to a Gamma distribution. More recently, the work in [9] showed that the aggregate power received at the center of a SCM from the nodes located in an annulus l can be also approximated by a Gamma distribution, when path-loss, fast fading and shadowing effects are considered. In our work, it is assumed the SCM described in [9].

Consequently, using the method of the moments, the shape and the scale parameters of the Gamma distribution that characterize the aggregate power received by N_{Tx} are given by

$$k_{\eta,l} = \text{E}[I_{\eta,l}]^2 / \text{Var}[I_{\eta,l}], \quad (2)$$

$$\theta_{\eta,l} = \text{Var}[I_{\eta,l}]/\text{E}[I_{\eta,l}], \quad (3)$$

where $\text{E}[I_{\eta,l}]$ and $\text{Var}[I_{\eta,l}]$ are the expectation and variance of the power received from the transmitters of the annulus l of the network η , which are respectively given by [9]

$$\text{E}[I_{\eta,l}] = 2\pi\lambda_{\eta,l}\tau_{\eta}P_{Tx_{\eta}}e^{\mu_{\xi}}\sqrt{e^{\sigma_{\xi}^2}}\left(\frac{(R_{\eta,l+1})^{2-m} - (R_{\eta,l})^{2-m}}{2-m}\right),$$

and

$$\begin{aligned} \text{Var}[I_{\eta,l}] = & \pi\lambda_{\eta,l}\tau_{\eta}P_{Tx_{\eta}}^2k_{\psi}\theta_{\psi}^2(1+k_{\psi}) \\ & \times \left(\frac{(R_{\eta,l+1})^{2-2m} - (R_{\eta,l})^{2-2m}}{1-m}\right). \end{aligned}$$

To derive the aggregate power received from all nodes of a given network, Υ_{η} , the summation of the power received from the L_{η} annuli must be considered. Let $\{Z_{\eta,l}\}_{l=1}^{L_{\eta}}$ be independent non-identically distributed (i.n.i.d.) Gamma RVs with parameters $k_{\eta,l}$ and $\theta_{\eta,l}$. The aggregate power received from the network Υ_{η} can be written as $I_{\eta} = \sum_{l=1}^{L_{\eta}} Z_{\eta,l}$. In the same way, the aggregate power received by all coexisting network is written as $I_{agg} = \sum_{\eta=1}^v I_{\eta}$, and represents the aggregate power caused by the nodes located within the L_N annuli of the v coexisting networks, with $L_N = vL_{\eta}$.

Let $\{Z_j\}_{j=1}^{L_N}$ be i.n.i.d. Gamma RVs with parameters k_j and θ_j , and $W_j \sim \text{Nakagami}(m_j, \Omega_j)$. The aggregate power can be written as $I_{agg} = \sum_{j=1}^{L_N} Z_j = \sum_{j=1}^{L_N} W_j^2$, since by definition $Z_j = W_j^2$, with $k_j = m_j$ and $\theta_j = \Omega_j/m_j$. According to [12], the sum of i.n.i.d. Nakagami- m RVs can be accurately approximated by an α - μ distribution. Consequently, the PDF of the aggregate power received from all transmitters of the coexisting networks (I_{agg}) can be approximated by an α - μ distribution as follows

$$f_{I_{agg}}(y) \approx \frac{\alpha\mu^{\mu}y^{\alpha\mu-1}}{\hat{r}^{\alpha\mu}\Gamma(\mu)} \exp\left(-\mu\frac{y^{\alpha}}{\hat{r}^{\alpha}}\right), \quad (4)$$

where $\hat{r} = \sqrt[\alpha]{\text{E}[Y^{\alpha}]}$, and $\mu = \frac{\hat{r}^{2\alpha}}{\text{Var}[Y^{\alpha}]}$. To compute $f_{I_{agg}}(y)$, the moment-based estimators for α and μ can be obtained from [12] as

$$\frac{\Gamma^2(\mu + 1/\alpha)}{\Gamma(\mu)\Gamma(\mu + 2/\alpha) - \Gamma^2(\mu + 1/\alpha)} = \frac{\text{E}^2[I_{agg}]}{\text{E}[I_{agg}^2] - \text{E}^2[I_{agg}]}, \quad (5)$$

and

$$\frac{\Gamma^2(\mu + 2/\alpha)}{\Gamma(\mu)\Gamma(\mu + 4/\alpha) - \Gamma^2(\mu + 2/\alpha)} = \frac{\text{E}^2[I_{agg}^2]}{\text{E}[I_{agg}^4] - \text{E}^2[I_{agg}^2]}. \quad (6)$$

The moments $E[I_{agg}]$, $E[I_{agg}^2]$, $E[I_{agg}^4]$ in (5) and (6), can be computed using the following multinomial expansion

$$E[I_{agg}^n] = \sum_{n_1=0}^n \sum_{n_2=0}^{n_1} \cdots \sum_{n_{L_N-1}=0}^{n_{L_N-2}} \binom{n}{n_1} \binom{n_1}{n_2} \cdots \binom{n_{L_N-2}}{n_{L_N-1}} \\ \times E[W_1^{2(n-n_1)}] E[W_2^{2(n_1-n_2)}] \cdots E[W_{L_N}^{2(n_{L_N-1})}],$$

where the Nakagami- m moments are given as

$$E[W_j^n] = \frac{\Gamma(k_j + n/2)}{\Gamma(k_j)} (\theta_j)^{n/2}.$$

Using the parameters α and μ , the parameter $\hat{r}$ can be estimated by

$$\hat{r} = \left[\frac{\mu^{2/\alpha} \Gamma(\mu) E[I_{agg}]}{\Gamma(\mu + 2/\alpha)} \right]^{1/2}. \quad (7)$$

Therefore, the harvested energy at the node N_{Tx} , E_h , is written as

$$E_h = \varsigma c T I_{agg}, \quad (8)$$

where $0 < \varsigma < 1$ represents the energy conversion efficiency, and the RV I_{agg} follows an α - μ distribution with α , μ and $\hat{r}$ computed from (5), (6), and (7).

IV. THROUGHPUT ANALYSIS

After having harvested energy during the harvesting period cT , the node N_{Tx} transmits data in the UL band with $P_{N_{Tx}}$ power, represented by

$$P_{N_{Tx}} = \frac{E_h}{(1-c)T} = \varsigma I_{agg} \frac{c}{(1-c)}. \quad (9)$$

Using (1), the signal-to-noise ratio (SNR) at the receiver node can be defined as

$$\gamma_d = \frac{P_{N_{Tx}} |h_1|^2}{d_1^m \sigma_{n_d}^2}, \quad (10)$$

where $\sigma_{n_d}^2$ is the variance of the zero-mean AWGN. Considering a Rayleigh channel with mean power $2\sigma_h^2$ between the nodes N_{Tx} and N_{Rx} , $|h_1|^2$ is exponentially distributed with parameter $1/(2\sigma_h^2)$. Given a SNR threshold γ_0 , the outage probability of the transmission can be written as

$$P_{out}(\gamma_0) = P(\gamma_d < \gamma_0) = \int_0^{\gamma_0} f_{\gamma_d}(z) dz. \quad (11)$$

Using (10), and considering the PDFs of I_{agg} and $|h_1|^2$, (11) can be rewritten as

$$P_{out}(\gamma_0) = \frac{\alpha \mu^\mu}{\hat{r}^{\alpha\mu} \Gamma(\mu)} \frac{1}{\Lambda} \int_0^{\gamma_0} \int_0^\infty \frac{1}{y} \left(\frac{z}{y} \right)^{\alpha\mu-1} \exp \left(\frac{-\mu z^\alpha}{(\hat{r} y)^\alpha} - \frac{1}{2\sigma_h^2 \Lambda} y \right) dy dz, \quad (12)$$

where

$$\Lambda = \frac{\varsigma c}{(1-c)d_1^m \sigma_{n_d}^2},$$

is the scaling value of the product of the RVs I_{agg} and $|h_1|^2$. Since the integral in (12) can only be numerically solved, we propose to approximate $P_{out}(\gamma_0)$ by an α - μ distribution as follows

$$P_{out}(\gamma_0) \approx \Gamma\left(\mu_p, \mu_p \left(\frac{\gamma_0}{\hat{r}_p \Lambda}\right)^{\alpha_p}\right) \frac{1}{\Gamma(\mu_p)}, \quad (13)$$

where α_p , μ_p and $\hat{r}_p$ can be obtained by solving the system of equations formed by (5), (6) and (7), substituting the symbols α , μ , $\hat{r}$, and $E[I_{agg}^n]$ by α_p , μ_p , $\hat{r}_p$, and

$$E[(I_{agg}|h_1|^2)^n] = n!(2\sigma_h^2 \hat{r})^n \frac{\Gamma(\mu + n/\alpha)}{\mu^{n/\alpha} \Gamma(\mu)}, \quad (14)$$

respectively. As will be seen, (13) shows to be a very tight approximation, being evaluated instantaneously. (14) represents the n -th moment of the product of the RVs I_{agg} and $|h_1|^2$. Assuming a communication rate $\mathcal{R}$ (in bits/T) and the transmission duration $(1-c)T$, the throughput of the communication channel between N_{Tx} and N_{Rx} can be written as

$$R_\tau(c) = (1 - P_{out}(\gamma_0))(1-c)\mathcal{R}. \quad (15)$$

From (15), one can notice that $(1 - P_{out}(\gamma_0))$ increases with c . However, the transmission duration decreases with c . This fact has motivated us to derive the optimal time allocation ratio,

$$c^* = \arg \max_{0 < c < 1} R_\tau(c), \quad (16)$$

which can only be computed in a numerical way, by finding the value c^* for which the following condition holds

$$\alpha_p (c^* \Gamma(\mu_p))^{-1} \exp\left(\mu_p \left(\frac{\gamma_0 d_1^m \sigma_{n_d}^2}{\hat{r}_p \varsigma} \frac{1-c^*}{c^*}\right)^{\alpha_p}\right) = 1 - (\Gamma(\mu_p))^{-1} \Gamma\left(\mu_p, \mu_p \left(\frac{\gamma_0 d_1^m \sigma_{n_d}^2}{\hat{r}_p \varsigma} \frac{1-c^*}{c^*}\right)^{\alpha_p}\right). \quad (17)$$

V. MODEL VALIDATION AND DISCUSSIONS

In this section, we validate the methodology described in Sections III and IV, by comparing the numerical results with simulations. We consider two coexisting networks ($v = 2$): a static network (Υ_1), and a network (Υ_2) where the nodes move according to the RWP. Three different mobility scenarios are analysed for Υ_2 , considering the case where nodes are static ($E[V] = 0$ m/s), or mobile with different average velocities ($E[V] = \{10.82, 1.50\}$ m/s). The parameters adopted in the validation are presented in Table I, which are divided in the parameters related with

the “Propagation Effects” described in Section II-B, the parameters of the network Υ_1 (“Static Network”), the parameters of the network Υ_2 (“Mobile Network”), and other parameters adopted in the WPC model (Section II-C), SCM, and simulations. The assessment of the model is carried out by comparing Monte Carlo simulation results with numerical results of the aggregate power (I_{agg} approximated by (4)), the throughput ($R_\tau(c)$ computed with (15)), and the optimal time allocation ratio (c^* computed with (17)). In the SCM, we have considered the same circular area for both networks Υ_1 and Υ_2 , i.e., $R_{1,1} = R_{2,1} = 20$ m, $R_{1,L_\eta+1} = R_{2,L_\eta+1} = 120$ m, and $\rho_1 = \rho_2 = 20$ m.

In Fig. 2, we compare the cumulative distribution function (CDF) of the aggregate power (I_{agg}) generated by the coexisting networks (Υ_1 and Υ_2) for the different mobility scenarios considered in network Υ_2 ($E[V] = \{10.82 \text{ m/s}, 1.50 \text{ m/s}, 0 \text{ m/s}\}$). Table II presents the α - μ

TABLE I
PARAMETERS ADOPTED IN THE SIMULATIONS.

Propagation Effects	P_{Tx_η}	10^3 mW	m	2
	σ_ξ	0.69	σ_h^2	1/2
	$\sigma_{n_d}^2$	0.01 mW		

Static Network (Υ_1)	$R_{1,1}$	20 m	$R_{1,L_\eta+1}$	120 m
	ρ_1	20 m	L_1	5
	λ_1 (node/m ²)	1×10^{-4}		

Mobile Network (Υ_2)	$R_{2,1}$	20 m	$R_{2,L_\eta+1}$	120 m
	ρ_2	20 m	L_2	5
	V_{min}	5 m/s	V_{max}	20 m/s
	n_2	100	τ_2	1
	$E[V]$	$\{10.82, 1.50, 0\}$ m/s	X_{max}	1000 m
	T_p	$\{0, 300, 3000\}$ s	Y_{max}	1000 m

Others	Monte Carlo samples	3×10^6	d_1	5 m
	γ_0	$\{-10, -5, 0, 5, 10, 15\}$ dB	ς	1
	L_N	10	v	2

distribution parameters adopted in (4) to approximate I_{agg} for the different average velocities $E[V]$. As can be seen, the numerical results (represented by the “Model” curves) are close to the results obtained through simulation. This indicates that the α - μ distribution in (4) can effectively approximate the distribution of I_{agg} with high accuracy. Moreover, we observe that the aggregate power increases with the mobility of the network Υ_2 , which is due to the higher density of nodes closer located to N_{Tx} as the node’s mobility increase [7].

TABLE II
PARAMETERS ESTIMATED FOR THE MODEL CURVES OF I_{agg} .

		α	μ	$\hat{r}$
Fig. 2	$E[V] = 10.82$ m/s	0.198	49.032	2.946
	$E[V] = 1.50$ m/s	0.263	19.548	1.881
	$E[V] = 0$ m/s	0.275	16.621	1.714




Fig. 2. CDF of the aggregate power when Υ_1 and Υ_2 coexist, and considering different average speeds of Υ_2 ’s nodes.

Next, we characterize the throughput (R_τ) achieved by the WPC system in the same coexisting scenarios adopted to obtain the results illustrated in Fig. 2. To this purpose, we have considered the optimal energy conversion efficiency of the energy harvesting process ($\varsigma = 1$),

the communication range $d_1 = 5$ m, and the SNR threshold $\gamma_0 = 5$ dB at the receiver. Moreover, it is assumed that N_{Tx} uses all the harvested energy to transmit the information. In Fig. 3, we present different curves of the throughput as a function of the time splitting ratio c . The numerical results (represented by the “Model” curves) have considered the approximation proposed in (13) to compute the outage probability. The parameters used in (13) were previously computed as described in Section IV, and their values for the different mobility scenarios are presented in Table III. The throughput, computed with (15), is close to the throughput obtained in the Monte Carlo simulations, as illustrated in Fig. 3. The results show that higher throughput values are achieved for higher mobility scenarios of the RWP network Υ_2 . This is because the amount of harvest energy increases with the velocity of the nodes of the network Υ_2 , as justified by the aggregate power results in Fig. 2. Moreover, it is shown that the parameter c effectively impacts on the achieved throughput, clearly identifying an upward where extending the harvesting period increases the transmission power, and a downward zone, where the extension of the harvesting period shortens the transmission period. The optimal point of operation is the one that divide the two zones.

TABLE III
PARAMETERS ESTIMATED FOR THE MODEL CURVES OF P_{out} .

		α_p	μ_p	$\hat{r}_p$
Fig. 3	$E[V] = 10.82$ m/s	0.316	6.098	2.199
	$E[V] = 1.50$ m/s	0.287	6.350	1.347
	$E[V] = 0$ m/s	0.284	6.288	1.216

To evaluate the optimal time allocation ratio (c^*) proposed in (17), we have considered the higher mobility scenario ($E[V] = 10.82$ m/s), and multiple SNR thresholds ($\gamma_0 = \{-10, -5, 0, 5, 10, 15\}$ dB). The simulation results of the throughput and the numerical results of the optimal time allocation ratio (c^*) are illustrated in Fig. 4 (a marker “o” was adopted to indicate the c^* value numerically computed with (17)). The throughput inversely increases with γ_0 , as expected. We also observe that γ_0 also impacts on the shape of the throughput curves. However, the optimal time allocation ratio is accurately approximated by (17) for all γ_0 values, as depicted in the figure.




Fig. 3. Throughput R_τ for the scenario considered in Fig. 2.




Fig. 4. Optimal time allocation ratio c^* for different SNR thresholds γ_0 .

REFERENCES

- [1] L. Irio, R. Oliveira, and D. B. da Costa, “Highly accurate approaches for the interference modeling in coexisting wireless networks,” *IEEE Commun. Lett.*, pp. 1–1, 2019.
- [2] Y. Gu and S. Aissa, “RF-based energy harvesting in decode-and-forward relaying systems: Ergodic and outage capacities,” *IEEE Trans. Wireless Commun.*, vol. 14, no. 11, pp. 6425–6434, Nov. 2015.
- [3] Y. Chen, “Energy-harvesting AF relaying in the presence of interference and Nakagami- m fading,” *IEEE Trans. Wireless Commun.*, vol. 15, no. 2, pp. 1008–1017, Feb. 2016.
- [4] I. Flint, X. Lu, N. Privault, D. Niyato, and P. Wang, “Performance analysis of ambient RF energy harvesting with repulsive point process modeling,” *IEEE Trans. Wireless Commun.*, vol. 14, no. 10, pp. 5402–5416, Oct. 2015.
- [5] Y. L. Che, L. Duan, and R. Zhang, “Spatial throughput maximization of wireless powered communication networks,” *IEEE J. Sel. Areas Commun.*, vol. 33, no. 8, pp. 1534–1548, Aug. 2015.
- [6] I. S. Gradshteyn and I. M. Ryzhik, *Table of Integrals, Series, and Products*, 7th ed. New York, NY, USA: Academic Press, 2007.
- [7] C. Bettstetter, G. Resta, and P. Santi, “The node distribution of the random waypoint mobility model for wireless ad hoc networks,” *IEEE Trans. Mobile Comput.*, vol. 2, no. 3, pp. 257–269, Jul. 2003.
- [8] L. Irio, R. Oliveira, and L. Bernardo, “Aggregate interference in random waypoint mobile networks,” *IEEE Commun. Lett.*, vol. 19, no. 6, pp. 1021–1024, Jun. 2015.
- [9] L. Irio, A. Furtado, R. Oliveira, L. Bernardo, and R. Dinis, “Interference characterization in random waypoint mobile networks,” *IEEE Trans. Wireless Commun.*, vol. 17, no. 11, pp. 7340–7351, Nov. 2018.
- [10] S. Al-Ahmadi and H. Yanikomeroglu, “On the approximation of the Generalized-K distribution by a Gamma distribution for modeling composite fading channels,” *IEEE Trans. Wireless Commun.*, vol. 9, no. 2, pp. 706–713, Feb. 2010.
- [11] M. Haenggi and R. K. Ganti, “Interference in large wireless networks,” *Found. Trends Netw.*, vol. 3, no. 2, pp. 127–248, Nov. 2009.
- [12] D. B. da Costa, M. D. Yacoub, and J. C. S. Santos Filho, “An improved closed-form approximation to the sum of arbitrary Nakagami- m variates,” *IEEE Trans. Veh. Technol.*, vol. 57, no. 6, pp. 3854–3858, Nov. 2008.