

Children's Online Handwriting Quality Analysis

Hanen Akouaydi ¹, Yahia Hamdi ², Houcine Boubaker ², Mourad Zaied ², Faouzi Alaya Cheikh ², and Adel Alimi ²

¹REGIM-Lab.: REsearch Groups in Intelligent Machines

²Affiliation not available

October 30, 2023

Abstract

An innovative e-learning project is presented in this paper, which is a mobile workbook that teaches handwriting at school. This mobile application proposes a new qualitative and quantitative analysis process of online cursive handwriting. It gives a real-time feedback, detects mistakes and helps teachers evaluate children's writing skills. The main aim of this notebook is to aid kids learn how to write correctly. We analyze handwriting according to major criteria like shape, kinematics of the trace, position respect to the reference lines,

stroke order and direction.

Children's Online Handwriting Quality Analysis.

Hanen Akouaydi, Yahia Hamdi, Houcine Boubaker, Mourad Zaid, Faouzi Alaya Cheikh, and Adel M. Alimi

Abstract—Contributions: An innovative e-learning project is presented in this paper, which is a mobile workbook that teaches handwriting at school. This mobile application proposes a new qualitative and quantitative analysis process of online cursive handwriting. It gives a real-time feedback, detects mistakes and helps teachers evaluate children's writing skills. The main aim of this notebook is to aid kids learn how to write correctly. We analyze handwriting according to major criteria like shape, kinematics of the trace, position respect to the reference lines, stroke order and direction.

Background: Beta-elliptic model with dissimilarity distance (DD) and similarity detection (SD), and SVM with Cartesian Fourier Descriptor Model (FDcarM) are used to analyze the handwriting quality. Our work apprehends dynamic and visual representations of the acquired traces, describes the overall geometry of a trace as a function of the undulations of its curvature function and selects efficient features adapted to various handwriting styles. This work demonstrates that beta-elliptic model is not only a model for segmentation and recognition but also a tool to evaluate handwriting. **Intended outcomes:** A master-class environment that motivates childrens to perform better on in application evaluations. The mobile workbook should be positively received by learners and teachers.

Application design: Our application provides interfaces for both learners and experts which are flexible with the particularity of each child and makes experienced kids engaged with challenging tasks.

Findings: For the validation of our proposed system, we collected a database of 400 Tunisian children from pre-schools and primary schools. Results demonstrate the efficiency and robustness of our application as the great majority of experts expressed a positive attitude toward it.

Index Terms—Children's Online Handwriting, Quality Analysis, Evaluation, Beta-elliptic model, Perceptual representation, Dynamic representation, Curvature presentation, Cartesian Fourier Descriptor Model (FDcarM), SVM.

I. INTRODUCTION

WITH pen-based tablet or finger, various criteria can be studied or analyzed like shape, pressure and direction. Our digital notebook gives immediately and personalized feedback to children and also to teachers who teach kids how to write. It also adopts a specific educational progression to each child. It is currently composed of Letter Writing, Word Writing, Digit Writing, Symbol Writing in Arabic/French/English

H.Akouaydi, Y.Hamdi, H.Boubaker and A.M.Alimi, REGIM-Lab.: Research Groups in Intelligent Machines, University of Sfax, National Engineering School of Sfax (ENIS), BP 1173, Sfax, 3038, Tunisia.

M.Zaid with RTIM-Lab: Research Team in Intelligent Machines, University of Gabes, National Engineering School of Gabes (ENIG), B.P. 6072, Gabes, Tunisia.

F.A.Cheikh is with The Norwegian Colour and Visual Computing Laboratory, Department of Computer Science, Norwegian University of Science and Technology, POBox 191, 2802, Norway

A.M.Alimi is also with Department of Electrical and Electronic Engineering Science, Faculty of Engineering and the Built Environment, University of Johannesburg, South Africa.

Corresponding author: Hanen Akouaydi.

Manuscript received June 14, 2021; revised .

as shown in Fig. 1. All evaluated writings are cursive. The evaluation process needs the segmentation of acquired traces into elliptic strokes and the extraction of beta-elliptic and Cartesian Fourier Descriptor parameters. We define reference models and we compare the child's trace by applying similarity and dissimilarity rules. The analysis evaluates the target symbol by comparing it with a model of reference. Our handwriting analyser system proposes finer analysis based on five metrics (direction, kinematics, order, shape, position respect to the reference lines). The assessor system is mainly based on Cartesian Fourier Descriptor model and beta-elliptic model. The plan of our paper is as follows: Section 2 reports some systems for handwriting analysis in literature. The architecture of our children's online handwriting analysis system is presented in section 3. Section 4 & 5 describe the different features used in analyzing children traces. Results are discussed in Section 6. Finally, section 7 concludes remarks about the future works.

II. RELATED WORKS

Handwriting quality is related to legibility and kinematics [1]. Three main skills are required in the writing process: a global visual representation of online script, identification of elementary strokes in it, and being able to generate a script as a group of elementary strokes respecting direction. The challenge of evaluation is more complex than recognition because we will not only evaluate the shape but also direction and order of writing. Children frequently make several kinds of errors: write correct shape in wrong direction or unversed, add addition strokes, letter or word transformation, etc. So, we have to be able to detect the kind of errors related to shape, order or direction. Handwriting recognition is the task of transforming language from graphical marks into meaningful representation. Humans are able to read or write easily. To analyze handwriting, we proceed by the detection of common properties, then we group together according to some laws like shape, direction, and order... The goal of this section is to illustrate theoretical approaches of handwriting analysis. In 2015, Bouillon et al [2] present a new work for evaluating handwriting of children (symbols, letters as an any geometric form) by using online fuzzy models. Simonnet et al. [3] proposed a multi-criteria approach for Latin handwriting quality analysis. In this work, the handwriting of children are evaluated by making compare with models using inter-class and intra-class scores. Indeed, a multi-criteria score describes the legibility (shape) and kinematic (order and direction). Likewise, in 2018, the authors [4] introduced an explicit segmentation approach for handwritten cursive word evaluation. First, the authors start by extracting the primary segmentation hypotheses. Next, they extract the letter hypotheses based on scoring and evaluation is based on

the fusion of elastic matching and writing analysis scores. In a recent work [5], Corbillé et al. combine different channels at the input of a single network to improve the classification performance of online children handwriting recognition. They convert the online trace into different image channels taking into account the dynamical information. Accadro et al. analyze handwriting kinematics of kids on tablets by dealing with different types of features (number of strokes per letter, pen down duration...) and shows that the handwriting is based on various kinematics characteristics like velocity and spatial grouping... [6] Only one work [7] deals with Chinese characters that identify 3 types of errors related to sequence stroke, stroke relationship and stroke production. Jolly et al. [8] compare the acquisition of traces from paper and tablets. This study encourage the using of digital devices in primary schools and preschools and the development of digital workbooks to assist teachers and children. A research [9] used five primitives to evaluate handwriting proficiency of children : legibility, form, alignment, size and space. An educational system [10] is used for handwriting teaching and repair by evaluating the quality of children handwritten letters. Other researchers are exploited the analyzing of children handwriting to identify children with dysgraphia [11]. A new study [12] shows that handwriting legibility improves with spelling ability more so than with the handwriting practice. It demonstrates also that the bilingual pupils had weaker spelling skills. The work of Boram and Choi [13] examines differences in children's graphomotor skills based on types of writing medium and gender. It approved that boys generated larger print sizes than girls and Preschoolers' graphomotor skills vary depending on writing support. Generally medical applications mainly deal with the kinematics features of handwriting in contrast with the educational systems that focus legibility criteria and use only the features of velocity and acceleration. The field of Arabic text evaluation is still an area of research for exploration because there is not any work dealing with this script. This work offers a writing experience at schools by using tablets (with stylus or finger touch). The experiments of this work were performed in primary schools and preschool Tunisian children. The paper presents results of the first experimentation in Tunisian primary schools with 400 children. During three-hour sessions, groups of six to eight kids as illustrated in Fig. 1, were writing letters, symbols, words and having automatic feedback. This application lets children work alone with real-time feedback. It proposes automatically pedagogical tasks that are personalized according to each child ability to write correctly or his difficulties based on its automatic writing analysis. It provides precise evaluation of kids writing (direction, shape, order) to aid experts in the automatic examination of kids writing skills and difficulties. The work demonstrates that beta-elliptic is not only a model for segmentation and recognition but also a tool to evaluate handwriting.

III. PROPOSED SYSTEM

Our system consists of evaluating children's writing based on various criteria such as shape, order and direction and gives immediately feedback. It is the combination of visual



Fig. 1. (a) Children's Handwriting Analysis project (b) First in-class experiment

regeneration by beta-elliptic model, and curvature description by Cartesian Fourier descriptor model (FDcarM) for characterizing the online trace. The system provides interfaces for learners and teachers. The main originality of the developed algorithm for children's handwriting quality assessment, consists of the adoption of multiple analysis criteria and the application of Beta-elliptic model and Cartesian Fourier descriptor model (FDcarM) to extract complementary and efficient feature vectors (see Fig. 2). The aim of our work is to help teachers with handwriting evaluation and return corrective feedback to children's schools during the learning process. Indeed, the handwritten sequences are online signals captured with digital devices. Next, five main criteria are utilized to evaluate the handwriting quality based on the combination of two models of handwriting modeling: Beta-elliptic model and FDcarM. Finally, a meaningful confidence score about each criterion is established for test samples depending on a principle method: comparison engine method based on similarity detection (SD) and measuring distance (MD) technique and SVM engines.

IV. SELECTION OF THE PERTINENT PARAMETERS

The evaluation of the quality of kids writing tests depends on the five criteria presented above. The proportional progression of scores for all criteria during the learning process is not guaranteed since kids often tends to focus on one or two criteria at the same time. The diversification of the evaluation criteria needs diversification of the parameters involved in the step of evaluation in order to refine their estimation and gives online feedback to the child and the teacher. The selection of the pertinent parameters to characterize each criterion is a very crucial step in the assessment process. Indeed, the visual and curvature generic features generated by FDcarM of the online trace that describe respectively the variation of the trajectory curvature function and the final view obtained post-drawing. For the criteria direction and order, we need to compare the succession of geometric and dynamic feature vectors of the strokes. Likewise, to evaluate the importance of the kinematics criterion in the handwriting learning process, we compare the velocity profile of the test script executed by the child to the trace models recorded by an expert. To do this, we have decided to use the dynamic part of the beta-elliptic model to characterize this criterion that evaluates quantitatively the correctness of a criterion characteristics of the trajectory A stroke which is limited by extremum velocity. Our system compares the traces produced by children with n correct traces named 'models', existing in the training database by using their features vectors.




Fig. 2. Architecture of our proposed system.

V. FEATURES EXTRACTION

The aim of this section is to illustrate the extracted features by Beta-elliptic model and Cartesian Fourier descriptor model (FDcarM) used for handwriting evaluation.

A. Preprocessing

Preprocessing is a primordial step for handwriting evaluation in order to obtain better analysis of children's handwriting traces. We remove trembling in writing, reducing hardware imperfections and banish inaccuracies in rapid pen-down/up detection. Chebyshev low pass filter is applied to decrease the noise and errors of temporal and spatial quantification caused by the acquisition system. In our analysis system, we avoid interpolation, adding missing points that can affect the direction information and gives bad representation of child script. All acquired traces should have the same scale so we have to apply normalization on the script (x, y) coordinates.

B. Beta-elliptic Features

Handwriting is movement, the sum of impulse signals as the response to the neuromuscular system according to the Beta function [14]. The Beta-elliptic model consists of decomposing the online trajectory into elliptic strokes based on the combination of the dynamic and geometric aspects [15]. Thus, handwriting can be decomposed into movements named strokes. Stokes are the result of superposition of time overlapped velocity profiles. Beta-elliptic model segments online script into different strokes by tracing Beta-elliptic parameters with their curvilinear velocity obeys this model. Equation (1) presents the Beta function:

$$\begin{cases} \beta(t, p, q, t_0, t_1) = \left(\frac{t-t_0}{t_c-t_0}\right)^p \left(\frac{t_1-t}{t_1-t_c}\right)^q, & \text{if } t \in [t_0, t_1[\\ \beta(t, p, q, t_0, t_1) = 0, & \text{if not} \end{cases} \quad (1)$$

where t_0 : starting time of Beta function.

t_c : is the instant when the curvilinear velocity reaches the amplitude of the inflexion point.

t_1 : the ending time of Beta function.

With $(p, q, t_0 < t_1) \in R$, and

$$t_c = \frac{p * t_1 + q * t_0}{p + q}, p = q * \frac{t - t_0}{t_c - t_1}$$




Fig. 3. Online handwriting modeling of Arabic character ص with (a).describes the velocity profile and (b).represents the geometric profile.

p, q intermediate parameters that influence on symmetry and width of Beta shape.

As a result, a stroke is presented by 10 parameters. For our analyser system, we use only 5 beta-elliptic parameters from ten that characterize each stroke. a, b, x_0, y_0 and θ describe the geometric features of handwriting and represent its static aspect. Theta parameter θ classify strokes into basic codes. The principal basic codes to write are: $-$, $/$, $|$, \backslash which can compose any script [16]. Those four perceptual codes are expanded to eight in order to identify the direction of elliptic stroke. Basic perceptual codes are not directly detectable so the step of segmentation by Beta-elliptic model is crucial. As a conclusion, handwriting is an arrangement of basic perceptual codes with numerous possible combinations of BPCs can form a similar letter or symbol but in evaluation we must pay attention to their directions.

$$\theta = \arctan\left(\frac{Y_1 - Y_0}{X_1 - X_0}\right) \quad (2)$$

In fact, the number of strokes is extracted automatically from the curvilinear velocity representation. Beta-elliptic arcs are presented in red in Fig. 3. a, b, x_0, y_0 and θ are the geometric-dynamic features of each elliptic stroke with its correspond basic code that describes the visual aspect, we form a vector feature of each elliptic stroke.

C. Cartesian Fourier descriptor model (FDcarM)

FDcarM represents one of the most precise approaches for modeling a trajectory or a closed contour [17]. To benefit from their robust approximation ability of periodic functions of the representation of online acquired traces, we have to convert the graphic signatures corresponding to the open trajectories of traces into periodic functions. M_1 and M_n are respectively the start point and the end point of the trajectory of a trace. This model is used to solve the problem of periodicity consists in traversing the trajectory of the trace come and back from M_1 to M_n and then from M_n to M_1 (see Fig. 4. a). For the DFcarM, the trajectory of an online script is represented by the two signature functions which respectively describe the variation of the abscissa x_i and the ordinate y_i of a current point M_i of the trajectory according to the curvilinear length l_i , calculated in Equation (3), traveled from the starting point M_1 .

$$l_i = \sum_{j=1}^i dL_j, \quad (3)$$

Where dL_i is the elementary curvilinear distance between the current point M_i and its previous point determined below in the Equation (4).

$$\begin{cases} dL_i = l_1 = 0, \\ dL_i = |M_i - M_{i-1}|, & \text{if } 1 < i \leq n \\ dL_i = |M_{2n-i+2} - M_{2n-i+1}| & \text{if } n+1 < i \leq 2n \end{cases} \quad (4)$$

The two functions $f_x(l_i)$, $f_y(l_i)$ and representing the Cartesian signature of a trace can adequately be approximated by Fourier series as long as they represent periodic (and symmetric) functions satisfying:

$f_x(l_1) = f_x(l_{2n}) = x_1$ abscissa of the trajectory at point M_1 ,
 $f_y(l_1) = f_y(l_{2n}) = y_1$ ordinate of the trajectory at point M_1 ,
 $f_x(l_i) = f_x(l_{2n-i+1}) = x_i$ abscissa of the trajectory at the current point M_i , $f_y(l_i) = f_y(l_{2n-i+1}) = y_i$ ordinate of the trajectory at the current point M_i , with $i=1, \dots, n$. The Fourier descriptor parameters which constitute the coefficients a_0 , a_j and b_j with $j=1, \dots, k$ of the Fourier series approximating the abscissa signature $x_i = f_x(l_i)$ at the k -th harmonic, are then calculated in Equations (5), (6) and (7). As well as the parameters the coefficients c_0 , c_j and d_j with $j = 1, \dots, k$ of the Fourier series approximating the ordinate signature $y_i = f_y(l_i)$, also at the k -th harmonic. Fig. 4. b presents the signature of Arabic letter Sad ص.

$$\begin{cases} a_0 = \frac{1}{2\pi} \cdot \sum_{j=1}^{2n} x_i * dL_i, \\ c_0 = \frac{1}{2\pi} \cdot \sum_{j=1}^{2n} y_i * dL_i \end{cases} \quad (5)$$

$$\begin{cases} a_j = \frac{1}{\pi} \cdot \sum_{i=1}^{2n} \cos(j \cdot \frac{2\pi l_i}{l_{2n}}) \cdot x_i \cdot dL_i, \\ b_j = \frac{1}{\pi} \cdot \sum_{i=1}^{2n} \sin(j \cdot \frac{2\pi l_i}{l_{2n}}) \cdot x_i \cdot dL_i \end{cases} \quad (6)$$

$$\begin{cases} c_j = \frac{1}{\pi} \cdot \sum_{i=1}^{2n} \cos(j \cdot \frac{2\pi l_i}{l_{2n}}) \cdot y_i * dL_i \\ d_j = \frac{1}{\pi} \cdot \sum_{i=1}^{2n} \sin(j \cdot \frac{2\pi l_i}{l_{2n}}) \cdot y_i * dL_i \end{cases} \quad (7)$$




Fig. 4. Trajectory of Arabic character and correspond signature functions approximated at the 8th harmonic.

For the reconstruction of the two signatures representing the trajectory, Fourier series use this approximation function presented in the Equation (8) below:

$$\begin{cases} x_i = f_x(l_i) \approx a_0 + \sum_{j=1}^{2n} [a_j \cos(j \cdot \frac{2\pi l_i}{l_{2n}}) + b_j \sin(j \cdot \frac{2\pi l_i}{l_{2n}})] \\ y_i = f_y(l_i) \approx c_0 + \sum_{j=1}^{2n} [c_j \cos(j \cdot \frac{2\pi l_i}{l_{2n}}) + d_j \sin(j \cdot \frac{2\pi l_i}{l_{2n}})] \end{cases} \quad (8)$$

The choice of the harmonic number k used in the Fourier descriptors is determined by a compromise between the precision of description of the model and its power of generalization. In fact, when the number of harmonics increases, the approximation of the Cartesian signature of online child script becomes more precise especially its resolution in number of points $i = 1, \dots, n$ is enough (the number of points n must be higher than $2k$). This precision makes better distinction between the modeled traces. However, when the precision increases further, the obtained model composed by the coefficients a_j , b_j , c_j and d_j will contain the noise introduced by the acquisition system at the level of the harmonics of high frequency or also data modeling the writing style specific to writer. The most relevant value of k for online handwriting recognition systems is fixed to $k = 8$ according to a statistical study.

VI. EXPERIMENTS AND RESULTS

The results of the assessor are reported in this section. Data-sets introduced are followed by the approach and the evaluation protocol. Then, results will be illustrated.

A. Data-sets

Data-sets are gathered from 400 children in Tunisian preschools. The data-set used to validate the efficiency and robustness of our application is collected by using five digital tablets. The constructed data-set comprises especially three subsets. Set 1 contains Arabic letters (i.e. ا, ت, ق, ذ, ي, ش, غ, خ, هـ, ز, و, ع, ث, ب, ت, ق, ن, ل, م, هـ, د, ذ, ر, ظ, ض, م, ر, ل, ر, ظ, ض) and Arabic words (باب سورة كورة, حاسوب, ثلج, جمل, مدرسة) selected from the primary textbook. In set 2, eight groups of similar Arabic letters relative to the shape (i.e. ذ, د, هـ, م, ل, ن, ق, ت, ب, ث, ع, و, غ, ع, ا, ث, ب, ت, ق, ن, ل, م, هـ, د, ذ, ر, ظ, ض, م, ر, ل, ر, ظ, ض). Set 3 are samples of cursive and non-cursive Latin characters. Besides, we have evaluated our system with 120 observations from set 4 which contains digits and symbols such as (&, Ω, Σ, \$, -, /, |, \, O...). Indeed,

20 correct samples for each sequence (letter, word, symbol) are used for training dataset with a few samples of incorrect shape, order and direction.

B. Setup

To study the efficient of our two mentioned models and their combination in handwriting quality evaluation, we have designed three groups of experiments. The first one is based on Beta-elliptic model using SD-DD comparison method. The second and is realized on FDcarM based on SVM classifier. Finally, the three test is fusion of the two previous tests. Beta-elliptic model extracts a set of pertinent features to characterize the five analysis criteria. The system determines for each criterion two thresholds: TCC and TCW delimiting respectively three evaluation zones: certainly correct (CC), Fuzzy (F), and certainly wrong (CW) presented in Fig. 5. The thresholds are calculated from two distributions distances DD_{CM} and DD_{WM} separating correct models and wrong ones respectively as demonstrated in Equation (9) and Equation (10).

$$T_{CC} = \min(Q_{DD_{CM}}(u_{max}), Q_{DD_{WM}}(u_{min})) \quad (9)$$

$$T_{CW} = \max(Q_{DD_{CM}}(u_{max}), Q_{DD_{WM}}(u_{min})) \quad (10)$$

Where $Q_D(u)$ is the value of the quantile function of the DD distribution at a cumulative probability of u percent. u_{max} and u_{min} are adjustable cumulative probabilities that limit the substantial part of the distribution DD fixed empirically to 96% and 4% respectively. A first normalized score NS_1 is assigned to the test sample relying on the correct partition using in Equation (11).

$$\begin{cases} NS_1 = 1, & \text{if } DD_{TM} < T_{CC} \\ NS_1 = 0, & \text{else if } DD_{TM} > T_{CW} \\ NS_1 = \frac{T_{CW} - DD_{TM}}{T_{CW} - T_{CC}} & \end{cases} \quad (11)$$

Similarly, we calculated the DD_{TW} distance separating the test sample from the set of wrong samples which represent the most common errors before converting them to a normalized score noted NS_2 between 0 and 1 analogously to Eq. 11. As described in Eq. 12, the final score NS is computed as the average between NS_1 and the complement of NS_2 .

$$NS = \frac{NS_1 + (1 - NS_2)}{2} \quad (12)$$

SVM model using FDcarM allows u to analyze three criteria: shape, direction, and order. Those criteria are the input for the multi-class SVM with RBF kernel function for making classification step. We evaluated the impact of the hybrid results of the two mentioned models. The final score attributed for each criterion is calculated as a weighted average of the scores assigned by each separate subsystem.

C. Results

In this section, we present the various levels of evaluation of our system and the different criteria used for analyzing traces




Fig. 5. Score Normalization.

1) *Type of Evaluation:* The global evaluation classify the test script into six classes (Correct, wrong Shape, Wrong order, Wrong direction, Irregular kinematic, Reference line surpass). With the value of distance between the test trace and models, the test script is evaluated correct or wrong. Table I sums up the global results achieved by our analyser system using the different feature extraction models. We can see from this table that our method is very effective for handwriting children's evaluation. In fact, it gives good results for characterizing the five criteria. The specific temporal information, geometric-perceptual parameters and curvature description provided by Beta-elliptic model (BEM) and FDcarM allow us to analyze all criteria. In fact, the final score assigned for each criterion is calculated as a weighted average of the scores assigned by each separate subsystem (Beta-elliptic system (BEM) and FDcarM system) weighted by its Correct Classification Rate (CCR).

The second type of evaluation provides a quantitative description of the test script by attributing for each criterion a quantitative evaluation label. It assigns a confidence score ranging from [0, 100] for each criterion as illustrated in Fig. 6 (red circle). The validation of our system is enhanced by a database gathered from Tunisian primary schools (letters, words and symbols). Obtained quantitative results of some observations are presented in Table 1. They demonstrate that the best confidence score of shape criterion is achieved by using FDcarM features rather than beta-elliptic features. This can be explained by the use of visual and curvature generic features generated by FDcarM. Moreover, the beta-elliptic approach is more accurate for the analysis of order and direction criteria than FDcarM. This robustness is due to the precise features to the change of direction and order of basic perceptual codes.

The third evaluation method provides a qualitative description of the test script by attributing for each criterion a qualitative evaluation label: (very well (VW), well (W), medium (M), bad (B), very bad (VB)) attributing according to the final score presented by green emoticon in blue rectangle in Fig. 6 and emoticons in Fig. 7.

2) *Criteria of Evaluation:* It is crucial to analyze the feedback of children about their first adventure with tablets. This experience with various criteria prove that kids get

TABLE I
OVERALL CCR [%] USING CORRECT/INCORRECT SAMPLES OF SHAPE, DIRECTION, ORDER AND KINEMATIC CRITERIA.

Criterion	Shape			Direction			Order			Kinematic
Models	BEM	FDcarM	Fusion	BEM	FDcarM	Fusion	BEM	FDcarM	Fusion	BEM
Arabic Characters	96,56	97,16	99,02	98,16	96,26	98,71	98,75	97,15	98,75	98,75
Arabic Words	94,13	96,50	97,96	97,10	96,13	98,61	97,62	95,35	97,84	97,20
Latin Characters	96,9	97,02	97,92	99,50	97,11	99,50	97,30	96,14	97,72	98,90
Symbols	97,13	98,02	99,41	98,13	98,08	99,12	98,20	96,10	99,15	98,60

TABLE II
QUANTITATIVE RESULTS OF SOME ARABIC, SCRIPTS AND SYMBOLS USING SHAPE, ORDER AND DIRECTION CRITERIA.

Criteria	Shape		Direction		Order	
Letters & Symbols	BEM	FDcarM	BEM	FDcarM	BEM	FDcarM
Arabic Letters						
ا	0,95	0,97	0,99	0,95	1	0,94
ب	0,97	0,98	0,96	0,94	0,91	0,94
ح	0,98	0,91	0,99	0,95	1	0,94
ع	0,93	0,97	1	0,95	0,97	0,94
س	0,94	0,99	0,99	0,95	0,92	0,94
Symbols						
Symbol -	0,98	0,97	0,99	0,97	1	1
Symbol /	0,95	0,97	0,99	0,95	1	1
Symbol	0,98	0,98	0,99	0,97	1	1
Symbol \	0,95	0,97	0,99	0,95	1	1
Symbol C	0,99	0,99	0,99	0,97	1	1
Latin Characters						
A	0,98	0,95	0,99	0,97	1	1
B	0,95	0,92	0,99	0,95	1	1
V	0,98	0,97	0,99	0,97	1	1
T	0,95	0,98	0,99	0,95	1	1
P	0,96	0,96	0,99	0,95	1	1
O	0,99	0,99	0,99	0,97	1	1
Arabic Words						
كرة	0,95	0,96	0,99	0,95	1	0,94
جبل	0,97	0,99	0,96	0,94	0,91	0,94
ثلج	0,98	0,97	0,99	0,95	1	0,94




Fig. 6. Quantitative & Qualitative Evaluation of Arabic Letter Haa هـ.




Fig. 7. Results of the shape criteria of Arabic letter Ba ب.

familiar with the workbook and to their score has gradually improved. Moreover, the personalized feedback lets children take steps forward with autonomy at their own speed. The specific temporal information and geometric-perceptual parameters provided by Beta-elliptic model allow us to analyze the five criteria (shape, direction, order, kinematic, and position). FDcarM characterizes (shape, direction, order) according to the handwriting velocity. Qualitative results of the shape criterion are summed up in Fig. 7 that present the qualitative evaluation of Arabic letter Baa ب. According to Table II, shape criterion is better evaluated with the curvature approach.

This can be explained by the use of visual and curvature generic features generated by FDcarM. The kind of shape errors are additional or missing strokes and contain strokes that disregard relative stroke proportions. A correct order of a trace must coincide with the order of the corresponding models. Recognition of the correct order is based on our four basic perceptual strokes. Thus, Table II shows a significant result of the direction criterion with the elliptic approach, which is more robust than the curvature approach in identifying the orientation stroke. The feedback given is based on multi-criteria. In fact, it depends mainly on legibility and ductus of teachers' models. The kinematic criterion lets us to distinguish the nature of

writing (fast or slow) based on elliptic approach. This is due to the use of dynamic parameters that give the overall temporal properties of the neuromuscular networks implicated in motion generation, and the geometric features of all the joints and muscles inducted to execute the movement. The elliptic model gives also an information about the position of the trace criterion.

To evaluate the performance of our proposed system com-



Fig. 8. Wrong Arabic Letter "Tad" ط .

paring to the state of the art, we didn't find any work deals with children's Arabic script. A mobile application presents the works of [2], [3] that gives only the opportunity to test Latin traces and imposes the use of stylus and specific version Android that is free for only one month. Thus, we can not test it.

VII. DETECTION & IDENTIFICATION OF CHILDREN'S ERRORS

Our proposed system is able to detect the children's errors. The several types of errors frequently made by children: write correct shape in wrong direction or versed, add additional strokes, letter or word transformation, etc. The challenge of evaluation is to identify the kind of errors. The incoming figures illustrate some sample of handwriting errors made by children. Those mistakes can be performed by our analysis application. Fig. 9 illustrates the Arabic letter **Seen** س with



Fig. 9. Arabic Letter "Seen" س with added strokes.

two additional strokes and Fig. 8 presents the Arabic letter **Tad** ط with missing stroke. We enrich our workbook with symbols in order to simplify the view of writing and instructional strategies for children with difficulties. For some children, decoding handwriting and making links between its parts is

very difficult task. So, we need to improve our workbook with simple symbols as illustrated in Fig. 10. With those symbols, children will be able to decompose into primitives and can also reproduce easily automatic flow of traces.




Fig. 10. Some symbols.

VIII. CONCLUSION

A new system for online handwriting evaluation and analysis is presented in this paper which deals with both cursive and non-cursive handwriting multi-script. It analyzes the handwriting quality of children and provides them real-time feedback based on basic criteria (direction, shape, order, position, kinematic). It uses the Beta-elliptic model for handwriting representation, that offers the possibility of detecting dynamic and geometric aspects in online handwriting trajectory modeling and the Cartesian Fourier descriptor model (FDcarM) for curvature description. We validate our system with databases collected from pre-schools which contained digits, letters Arabic/Latin, symbols. Results prove the effectiveness of the proposed system that aids experts and learners by giving feedback during the handwriting assessment process. The extracted features are universal and can be extracted from other scripts. They can be adapted for other applications such as the pre-diagnosis of neuromuscular pathologies and the difficulties of dyslexia and dysgraphia.

ACKNOWLEDGMENT

The research leading to these results has received funding from the Ministry of Higher Education and Scientific Research of Tunisia under the grant agreement number LR11ES48.

REFERENCES

- [1] L. H. Dinehart, "Handwriting in early childhood education: Current research and future implications," *Journal of Early Childhood Literacy*, p. 97–118, 2015.
- [2] M. Bouillon and E. Anquetil, "Handwriting analysis with online fuzzy models," *Conference of the International Graphonomics Society*, p. 71–74, 2015.
- [3] D. Simonnet, E. Anquetil, and M. Bouillon, "Multi-criteria handwriting quality analysis with online fuzzy models," *Pattern Recognition*, p. 31, 2017.
- [4] D. Simonnet, N. Girard, E. Anquetil, M. Renault, and S. Thomas, "Evaluation of children cursive handwritten words for e-education," *Pattern Recognition Letters*, p. 11, 2018.
- [5] S. Corbillé, E. Fromont, E. Anquetil, and P. Nerdeux, "Integrating writing dynamics in cnn for online children handwriting recognition," *17th International Conference on Frontiers in Handwriting Recognition (ICFHR)*, 2020.
- [6] A. P. Accardo, M. Genna, and M. Borean, "Development, maturation and learning influence on handwriting kinematics," *Human movement science*, p. 11, 2013.

- [7] C. W. Li-Tsang, A. S. Wong, H. W. Leung, J. S. Cheng, B. H. Chiu, F. Linda, and R. C. Chung, "Validation of the chinese 530 handwriting analysis system (chas) for primary school students in hong kong," *Research in developmental disabilities*, p. 2872–2883, 2013.
- [8] C. Jolly, R. Palluel-Germain, and E. Gentaz, "Evaluation of a tactile training for handwriting acquisition in french kindergarten children: A pilot study," *Kindergartens: Teaching methods, expectations and current challenges*, p. 161–176, 2013.
- [9] T. H. Falk, C. Tam, H. Schellnus, and T. Chau, "On the development of a computer-based handwriting assessment tool to objectively quantify 535 handwriting proficiency in children," *Computer Methods and Programs in Biomedicine*, p. 102–111, 2011.
- [10] V. Kulesh, K. Schaffer, I. Sethi, and M. Schwartz, "Handwriting quality evaluation," *Proceedings of the Second International Conference on Advances in Pattern Recognition, ICAPR*, pp. 157–165, 2001.
- [11] T. Gargot, T. Asselborn, H. Pellerin, I. Zammouri, S. M. Anzalone, L. Casteran, W. Johal, P. Dillenbourg, D. Cohen, and C. Jolly, "Acquisition of handwriting in children with and without dysgraphia: A computational approach," *PLoS ONE 15(9):e0237575*, p. 22, 2020.
- [12] C. Markéta, D. Cameron, H. C. Leah, and W. Caspar, "Handwriting legibility and its relationship to spelling ability and age: Evidence from monolingual and bilingual children," *Frontiers in Psychology*, p. 16, 2020.
- [13] N. Boram and C. Naya, "Differences in graphomotor skills by the writing medium and children's gender," *Education Sciences*, p. 12, 2021.
- [14] M. Alimi, "An evolutionary neuro-fuzzy approach to recognize online arabic handwriting," *Proceedings of the Fourth International Conference on Document Analysis and Recognition*, p. 382–386, 1997.
- [15] Y. Hamdi, H. Boubaker, T. Dhieb, A. Elbaati, and A. M. Alimi, "Hybrid dbilstm-svm based beta-elliptic-cnn models for online arabic characters recognition," *ICDAR*, pp. 545–550, 2019.
- [16] H. Akouaydi, S. Njah, W. Ouarda, A. Samet, M. Zaied, and A. M. Alimi, "Convolutional neural networks for online arabic characters recognition with beta-elliptic knowledge domain," in *ICDARW2019*, no. 6, 2019.
- [17] P. Eric and F. King-Sun, "Shape discrimination using fourier descriptors," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. PAMI, pp. 388–397, 1986.



Hanen Akouaydi is currently a PhD student in computer science at the National School of Engineers of Sfax. She obtained her engineering degree in Computer Science from Higher Institute of Multimedia Arts of Manouba in 2012. Her research interests include online handwriting recognition and deep learning. She is a member of the IEEE Student and the IEEE Computer Society and affiliates to REGIM Laboratory.



Yahia Hamdi is a PhD student at the National School of Engineering of Sfax, Tunisia. He obtained the master degree in computer science from the University of Sfax in 2012. His research focused on the area of online Handwriting recognition and handwriting trajectory modeling. He is a member of the IEEE Student and affiliates to REGIM Laboratory.



Houcine Boubaker Graduated from Electrical Engineering Department in 1995. He obtained his master degree in systems analyses and digital signal processing in 1997. He earned the Ph.D. degree in Electrical & Computer Engineering from the University of Sfax. His research interest includes trajectory modeling and applications of intelligent methods to pattern recognition. He is an IEEE student member.



Mourad Zaied actually a Professor at the National School of Engineers of Gabes. He earned the Ph.D. degree and then the HDR both in Electrical and Computer Engineering in 2013. He is IEEE Senior member since 2000. He received his HDR, and his Ph.D degrees in Computer Engineering and the Master of science from the National Engineering School of Sfax respectively in 2013, 2008 and in 2003. He obtained the degree of Computer Engineer from the National Engineering School of Monastir in 1995. Since 1997 he served in several institutes and faculties in the university of Gabes as teaching assistant. His research interests include Computer Vision and Image and video analysis. These research activities are centered on Wavelets and Wavelet networks and their applications to data classification and approximation, pattern recognition and image, audio and video coding and indexing. He is the director of RTIM-Lab.



Faouzi Alaya Cheikh is currently a Professor at Norwegian University of Science and Technology (NTNU), Norway. His research interests include e-Learning, 3D imaging, image and video processing and analysis, video-surveillance, behaviour analysis, biometrics, video-guided intervention, image guided navigation and content-based retrieval. He is member of the Norwegian Colour and Visual Computing Laboratory (Colourlab).



Adel M. Alimi is currently a Professor at the National School of Engineers of Sfax. He received the Ph.D. degree and then the HDR both in Electrical and Computer Engineering in 1995 and 2000 respectively. His research interest includes applications of intelligent methods and vision systems. He was guest editor of several special issues of international journals like Soft Computing. He is IEEE Senior member since 2000 and he is the director of REGIM Laboratory.